



TP-Link Omada EAP650-Outdoor 3000 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link

Product family: Omada

Product code: EAP650-OUTDOOR

Product name : EAP650-Outdoor

TP-Link Omada EAP650-Outdoor. 2,4 GHz, 5 GHz, Andmete edastamise maksimaalne määr: 3000 Mbit/s. Turvaalgoritmid: WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge



| Funktsioonid | | Pesad & liidesed | |
|--|---|---|-------------------|
| 2,4 GHz * | ✓ | Ethernet LAN (RJ-45) pordid * | 1 |
| 5 GHz * | ✓ | Võimsus | |
| 6 GHz * | ✗ | Power over Ethernet tugi * | ✓ |
| Andmete edastamise maksimaalne määr * | 3000 Mbit/s | Disain | |
| Maksimaalne andmeedastuskiirus (2.4 GHz) | 574 Mbit/s | Paigutus * | Post, Sein |
| Maksimaalne andmeedastuskiirus (5 GHz) | 2402 Mbit/s | Toote värv * | Valge |
| Ethernet LAN-i andmeedastuskiirused | 10,100,1000 Mbit/s | Rahvusvahelise kaitse (IP) kood | IP67 |
| | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at | Lähtestusnupp | ✓ |
| Võrgustandardid | | LED-indikaatorid | ✓ |
| Kaabeldustehnoloogia | 10/100/1000Base-T(X) | Sertifikaat | CE, FCC, RoHS |
| Kasutajate arv | 250 kasutaja(t) | Antenn | |
| Automaatne kanalivalik | ✓ | Antenni tüüp * | Sisemodem |
| Automaatne kanalite otsing | ✓ | Antenni suuna tüüp | Mitmesuunaline |
| MIMO | ✓ | Kaal ja mõõtmed | |
| MIMO tüüp | Multi User MIMO | Laius | 280,4 mm |
| Fit AP režiimi elemendid | Silmusvõrgud | Sügavus | 106,5 mm |
| VLAN-i tugi | ✓ | Kõrgus | 56,8 mm |
| Kiiruse piiramine | ✓ | Pakendi sisu | |
| Band Steering | ✓ | Kaasnevate toodete arv | 1 tk |
| Airtime Fairness (ATF) | ✓ | Paigalduskomplekt | ✓ |
| Teenusekvaliteedi (QoS) tugi | ✓ | Kiirstardi juhend | ✓ |
| BeamForming | ✓ | Töötingimused | |
| Turvalisus | | Suhteline õhuniiskus kasutamisel (H-H) | 10 - 90 protsenti |
| Turvaalgoritmid * | WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, WPA3, WPA3-Enterprise | Kasutamistemperatuur (T-T) | -30 - 70 °C |
| MAC-aadresside filtreerimine | ✓ | Hoiustamistemperatuur (T-T) | -40 - 70 °C |
| Service Set Identifier (SSID) elemendid | Multiple SSIDs, SSID-edastus sees/väljas | Suhteline õhuniiskus (H-H) hoiustamisel | 5 - 90 protsenti |



4897098682098



4897098683552



0840030703553



840030703553

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.