

## MSI MAG CORELIQUID 360R V2 arvuti jahutussüsteem Emaplaat, Protssessor Vedeljahutuskomplekt 12 cm Must



**Brand :** MSI

**Product code:** MAG CORELIQUID 360R V2

**Product name :** MAG CORELIQUID 360R V2

MSI MAG CORELIQUID 360R V2. Tüüp: Vedeljahutuskomplekt, Ventilatori läbimõõt: 12 cm, Pöörlemiskiirus (min): 500 RPM, Pöörlemiskiirus (max): 2000 RPM, Maksimaalne õhuvool: 78,73 cfm, Minimaalne õhusurve: 0,23 mmH2O, Maksimaalne õhusurve: 2,39 mmH2O, Laagri tüüp: Kuullaager. Toote värv: Must

Toimimine		Disain	
Sobiv asukoht *	Emaplaat, Protssessor	Toote värv *	Must
Tüüp *	Vedeljahutuskomplekt	Radiaatori materjal	Alumiinium
Ventilaatori läbimõõt	12 cm	Ventilaatorite arv	3 ventilaator(id)
	LGA 1150 (pesa H3), LGA 1151 (pesa H4), LGA 1155 (Socket H2), LGA 1156 (Socket H), LGA 1200 (Socket H5), LGA 1366 (Socket B), LGA 1700, LGA 2011 (Socket R), LGA 2011-v3 (Socket R), LGA 2066, Pistikupesa AM2, Pistikupesa AM2+, Pistikupesa AM3, Socket AM3+, Pesa AM4, Socket FM1, Socket FM2, Socket FM2+, Socket SP3, Socket TR4, Socket sTRX4	LED-taustvalgustus	✓
Toetatud protssessoripesad	AMD Ryzen 7 5th Gen, 3rd Generation AMD Ryzen™ 9, AMD Ryzen 9 5th Gen, AMD Ryzen Threadripper 3rd Gen, Intel® Core™ i7, Intel® Core™ i9	Ventilaatori konektor	4-sooneline
Ühilduvad protssessoriseeriad		<b>Võimsus</b>	
Pöörlemiskiirus (min)	500 RPM	Ventilaatori võimsustarve	1,8 W
Pöörlemiskiirus (max)	2000 RPM	Pumba võimsustarve	4,08 W
Minimaalne õhuvool	21,63 cfm	Pumba pingeline	12 V
Maksimaalne õhuvool	78,73 cfm	Pumba vool	340 mA
Minimaalne õhusurve	0,23 mmH2O	Ventilaatori pingeline	12 V
Maksimaalne õhusurve	2,39 mmH2O	Ventilaatori vool	0,15 A
Ventilaatori läbimõõt 2	12 cm	<b>Kaal ja mõõtmed</b>	
Impulsi-laiuse modulatsiooni (PWM) tugi	✓	Radiaatori laius	39,4 cm
Laagri tüüp	Kuullaager	Radiaatori sügavus	12 cm
Ventilaatori müratase (min)	14,3 dB	Radiaatori kõrgus	2,7 cm
Ventilaatori müratase (max)	34,3 dB	Toru pikkus	40 cm
Pumba müratase	18 dB	Veeploki laius	8,06 cm
Ventilaatori laagri tehnoloogia	Kuullaager	Veeploki sügavus	6,68 cm
Pumba laagritehnoloogia	Keraamiline kuullaager	Veeploki kõrgus	4,86 cm
Pumba ühendaja	3-sooneline	Ventilaatori mõõdud (laius x sügavus x kõrgus)	120 x 120 x 25 mm
Pumba mootori kiirus	4200 RPM	<b>Logistika andmed</b>	
Ventilaatori kiirus (min)	500 RPM	Harmonized System (HS) kood	84733080
Ventilaatori kiirus (max)	2000 RPM		



4526541039089

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date