



Dahua Technology XVR5116H-4KL-I3 DVR-salvesti Must

Brand : Dahua Technology

Product code: XVR5116H-4KL-I3

Product name : XVR5116H-4KL-I3



Dahua Technology XVR5116H-4KL-I3. Toote värv: Must, Maksimaalne video resolutsioon: 3840 x 2160 pikslit, Videopakkimise formaadid: H.264, H.264+, H.265, H.265+. Video sisendkanalid: 16 kanalid. Ethernet-liidese tüüp: Gigabit Ethernet, Toetatud võrguprotokollid: HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P. Kõvaketta liides: SATA, Maksimaalne kõvakettamaht: 16 TB. Toite tüüp: DC (alalisvool), Alalisvoolu ping: 12 V, Võimsustarve (tüüpiline): 15 W

Toimimine		Pesad & liidesed	
Maksimaalne video resolutsioon	3840 x 2160 pikslit	VGA (D-Sub) väljundpordid	1
Videopakkimise formaadid	H.264, H.264+, H.265, H.265+	USB 2.0 portide arv	2
Toetatud audioformaadid	G.711 A-law, G.711 µ-law, PCM	USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk	1
Sisemine	✗	RS-485 pordid	1
Varundamise funktsioon	✓	Võrgustumine	
Video salvestamise kiirus	30 fps	Ethernet LAN	✓
Videohõive kiirus (PAL)	25 fps	Ethernet-liidese tüüp	Gigabit Ethernet
Videohõive kiirus (NTSC)	30 fps	Ethernet LAN (RJ-45) pordid	1
Video kaotuse tuvastamine	✓	Toetatud võrguprotokollid	HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P
Video liikumisandur	✓	Kõvaketas	
Kanalite arv	16 kanalid	Toetatud kõvaketaste arv	1
Toote värv *	Must	Kõvaketta liides	SATA
Taasesitusrežiimid	Kohene, Üldkasutus, Event, Tag, Nutikas	Maksimaalne kõvakettamaht	16 TB
Analoogsignaali vormingu süsteem	NTSC, PAL	Protsessor	
Installitud operatsioonisüsteem	Kaasas LINUX	Sisesehitatud protsessor	✓
Helisüsteem	kahe-suunaline	Võimsus	
Heli sisendkanalid	1 kanalid	Toite tüüp	DC (alalisvool)
Audioväljundi kanalid	1.0 kanalid	Alalisvoolu ping	12 V
Maksimaalne kaadrisagedus	60 fps	Võimsustarve (tüüpiline)	15 W
USB ühilduvus	✓	Kaal ja mõõtmed	
Toetatud multi-ekraan	✓	Laius	325 mm
Multi-ekraani režiimid	1, 4, 8, 9, 16, 25, 36	Sügavus	257,1 mm
Liikumisandur	✓	Kõrgus	55 mm
Video voogesitus	✓	Kaal	1,23 kg
Dual stream tugi	✓	Pakendi andmed	
Bitisagedus	32 Kbit/s	Pakendi laius	372 mm
Püstiku mahutavus	1U	Pakendi sügavus	117 mm
Pesad & liidesed		Pakendi kõrgus	308 mm
Video sisendkanalid	16 kanalid	Pakendi kaal	2,11 kg
BNC-sisendpordid	16	Töötingimused	
HDMI-portide arv	1	Kasutamistemperatuur (T-T)	-10 - 55 °C
		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-AUG-2024. Prints or copies of Information are only valid on the printed Publication date