



Dahua Technology Access PFS3005-5GT-V2 Mittejuhitav L2 Gigabit Ethernet (10/100/1000) Must

Brand : Dahua Technology

Product family: Access

Product code: DH-PFS3005-5GT-V2



Product name : PFS3005-5GT-V2

Dahua Technology Access PFS3005-5GT-V2. Lüliti tüüp: Mittejuhitav, Lüliti kiht: L2. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 5. MAC-aadresside tabel: 2000 sisestust, Lülitusvõime: 10 Gbit/s. Alalisvoolu sisendpinge: 5 V. Toitepistmik: Alaldi sisendi pesa



| Juhtimisfunktsioonid | | Tehnilised andmed | |
|---|---------------------------------|---|---|
| Lüliti tüüp * | Mittejuhitav | Vastavussertifikaadid | CE, Föderaalne kommunikatsioonikomisjon (FCC) |
| Lüliti kiht | L2 | | |
| Pesad & liidesed | | Võimsus | |
| RJ-45 Etherneti ühenduse pesade arv * | 5 | Toiteallikas * | DC (alalisvool) |
| RJ-45 Etherneti ühenduse pesade tüüp * | Gigabit Ethernet (10/100/1000) | Kaasas toiteplokk * | ✓ |
| Gigabitise Etherneti (vask) portide arv | 5 | Alalisvoolu sisendpinge | 5 V |
| Toitepistmik | Alaldi sisendi pesa | Sisendvool | 1 A |
| Võrgustumine | | Elektritarbimine (max) | 1,5 W |
| 10G-tugi * | ✗ | Internet elektrivõrgu kaudu (PoE) | |
| Etherneti vaskaablite tehnoloogia | 10BASE-T, 100BASE-T, 1000BASE-T | Power over Ethernet tugi * | ✗ |
| Andmeedastus | | Töötingimused | |
| Lülitusvõime * | 10 Gbit/s | Kasutamistemperatuur (T-T) | 0 - 45 °C |
| Edastamise kiirus | 7,44 Mpps | Hoiustamistemperatuur (T-T) | -40 - 70 °C |
| MAC-aadresside tabel * | 2000 sisestust | Suhteline õhuniiskus kasutamisel (H-H) | 5 - 95 protsenti |
| Paketi puhvermälu | 1,5 MB | Suhteline õhuniiskus (H-H) hoiustamisel | 5 - 95 protsenti |
| Disain | | Kaal ja mõõtmed | |
| Püstikmontaaž * | ✗ | Laius | 47 mm |
| Toote värv | Must | Sügavus | 87 mm |
| Korpuse materjal | Metall | Kõrgus | 22 mm |
| LED-indikaatorid | ✓ | Kaal | 160 g |
| Toimimine | | Pakendi andmed | |
| Keskmine tõrkeintervall (MTBF) | 3184161,84 h | AC-adapter kaasa arvatud | ✓ |
| | | Pakendi laius | 111 mm |
| | | Pakendi sügavus | 94 mm |
| | | Pakendi kõrgus | 67 mm |
| | | Pakendi kaal | 280 g |
| | | Jätkusuutlikkus | |
| | | Jätkusuutlikkuse järgimine | ✓ |



6923172582027

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 19-AUG-2024. Prints or copies of Information are only valid on the printed Publication date