

ASUS ROG STRIX 1000W Gold (16-pin cable) toiteallika komponent 20+4 pin ATX ATX Must

Brand : ASUS

Product code: 90YE00AA-B0NA00

Product name : ROG STRIX 1000W Gold (16-pin cable)

ASUS ROG STRIX 1000W Gold (16-pin cable). Koguvõimsus: 1000 W, AC-sisendpinge: 100 - 240 V, Kombineeritud võimsus (+3,3 V): 125 W. Emaplaadi toitepistik: 20+4 pin ATX, Emaplaadi toitekaabli pikkus: 61 cm, SATA toitekaabli pikkus: 400,120,410,150 mm. Otstarve: PC, Toiteploki (PSU) standard: ATX, 80 PLUS sertifikaat: 80 PLUS Gold. Toote värv: Must, Jahutuse tüüp: Aktiivne, Ventilaaatori läbimõõt: 13,5 cm. Kaablid kaasa arvatud: CPU, PCIe, SATA, Peripheral (Molex)



Võimsus		Pesad & liidesed	
Koguvõimsus *	1000 W	PCI Expressi toitepistikud (16 kontaktiga)	1
AC-sisendpinge *	100 - 240 V	PCI Express toitekaabli pikkus	67,5 cm
Kombineeritud võimsus (+3,3 V)	125 W	CPU-toitepistik (4 + 4 kontakti)	✓
Kombineeritud võimsus (+12 V)	996 W	CPU toitekaabli pikkus	100 cm
Kombineeritud võimsus (+5 V)	125 W	Kaabelduse tüüp	Täielikult modulaarne
Kombineeritud võimsus (-12 V)	3,6 W	Toimimine	
Kombineeritud võimsus (+5 Vsb)	15 W	80 PLUS sertifikaat *	80 PLUS Gold
Maksimaalne väljundvool (+3,3 V)	25 A	Otstarve *	PC
Maksimaalne väljundvool (+12 V)	83 A	Toiteploki (PSU) standard *	ATX
Maksimaalne väljundvool (+5 V)	25 A	Vaikne režiim	✓
Maksimaalne väljundvool (-12 V)	0,3 A	Laagertehnoloogia	DBB
Maksimaalne väljundvool (+5 Vsb)	3 A	Disain	
Toite kaitsefunktsioonid	Ülevool, Ülevõimsus, Ülepinge, Ülekütmine, Lühis, Alapinge	Toote värv	Must
Pesad & liidesed		Jahutuse tüüp	Aktiivne
Emaplaadi toitepistik *	20+4 pin ATX	Ventilaatori läbimõõt	13,5 cm
Emaplaadi toitekaabli pikkus	61 cm	Ventilaatorite arv	1 ventilaator(id)
SATA-toitepistikute arv	8	Ventilaatori paiknemine	Ülaosa
SATA toitekaabli pikkus	400,120,410,150 mm	Valgustus	✓
Välisseadmete (Molex) toitepistikud (4 kontakti) *	4	Pakendi sisu	
Välise (Molex) toitekaabli pikkus	450,120 mm	Kaablid kaasa arvatud	CPU, PCIe, SATA, Peripheral (Molex)
PCI Expressi toitepistikud (6 + 2 kontakti)	3	Kaal ja mõõtmised	
		Laius	160 mm
		Sügavus	150 mm
		Kõrgus	86 mm
		Kaal	1,88 kg

Pakendi andmed	
Pakendi laius	310 mm
Pakendi sügavus	180 mm
Pakendi kõrgus	115 mm
Pakendi kaal	3,54 kg
Pakendi tüüp	Karp
Tehnilised andmed	
Vastavussertifikaadid	RoHS



4711387246115

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date