



TP-Link TL-SG1210PP võrgulüli Mittejuhitav Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product code: TL-SG1210PP

Product name : TL-SG1210PP



TP-Link TL-SG1210PP. Lüli tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 10. MAC-aadresside tabel: 4000 sisestust, Lülitusvõime: 20 Gbit/s. Võrgustandardid: IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Power over Ethernet tugi



Juhtimisfunktsioonid		Toimimine	
Lüli tüüp *	Mittejuhitav	Ilma ventilaatorita	✓
Teenusekvaliteedi (QoS) tugi	✓	Võimsus	
Pesad & liidesed		Toiteallikas *	DC/PoE
RJ-45 Etherneti ühenduse pesade arv *	10	Kaasas toiteplokk *	✓
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Toiteallikate arv	1
Gigabitise Etherneti (vask) portide arv	10	AC-sisendpinge	90 - 220 V
Kombineeritud SFP-pesade arv	1	AC-sisendsagedus	50 Hz
Võrgustumine		Sisendvool	2.43 A
Võrgustandardid *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Sisendpinge	53.5 V
10G-tugi *	✗	Elektritarbimine (max)	144,1 W
Etherneti vaskaablite tehnoloogia	10BASE-T, 100BASE-TX	Internet elektrivõrgu kaudu (PoE)	
Toetatud kaablitüübid	Cat3, Cat4, Cat5, Cat5e	Power over Ethernet tugi *	✓
Voo reguleerimise tugi	✓	Toide üle võrgu (PoE) pesade arv	2
Auto MDI/MDI-X	✓	Etherneti toitega 4PPoE (PoE++) portide kogus	6
Automaatne ühildumine	✓	Toide üle võrgu (PoE) võimsusühikuid kokku	123 W
Automaatse MAC-aadressi tuvastamise tugi	✓	Töötingimused	
Automaatse MAC-aadressi aegumise tugi	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Andmeedastus		Hoiustamistemperatuur (T-T)	-40 - 70 °C
Lülitusvõime *	20 Gbit/s	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Edastamise kiirus	14,88 Mpps	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
MAC-aadresside tabel *	4000 sisestust	Soojuse hajumine	482,17 BTU/h
Ladusta-ja-edasta	✓	Kaal ja mõõtmed	
Turvalisus		Laius	209 mm
IGMP-jälgimine	✓	Sügavus	126 mm
		Kõrgus	26 mm
		Pakendi andmed	
		Kaablid kaasa arvatud	Vahelduvvool

Disain		Pakendi andmed	
Püstikmontaaž *	✘	Kasutusjuhend	✓
Toote värv	Must	Pakendi tüüp	Karp
Korpuse materjal	Teras	Logistika andmed	
LED-indikaatorid	✓	Harmonized System (HS) kood	85176990
Sertifikaat	FCC, CE, RoHS		



4895252500356



4895252500349

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date