



TP-Link LiteWave LS105GP võrgulüliti Mittejuhitav Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product family: LiteWave

Product code: LS105GP

Product name : LS105GP



TP-Link LiteWave LS105GP. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 5. MAC-aadresside tabel: 2000 sisestust, Lülitusvõime: 10 Gbit/s. Võrgustandardid: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Alalisvoolu sisendpinge: 53.5 V. Power over Ethernet tugi



Juhtimisfunktsioonid		Võimsus	
Lüliti tüüp *	Mittejuhitav	Toiteallikas *	DC/PoE
Teenusekvaliteedi (QoS) tugi	✓	Kaasas toiteplokk *	✓
Pesad & liidesed		AC-sisendpinge	220 V
RJ-45 Etherneti ühenduse pesade arv *	5	AC-sisendsagedus	50 Hz
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Alalisvoolu sisendpinge	53.5 V
Võrgustumine		Elektritarbimine (max)	74,46 W
Võrgustandardid *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Internet elektrivõrgu kaudu (PoE)	
10G-tugi *	✗	Power over Ethernet tugi *	✓
Toetatud kaablitüübid	Cat3, Cat5e, Cat4, Cat5	Toide üle võrgu (PoE) pesade arv	4
Voo reguleerimise tugi	✓	Toide üle võrgu (PoE) võimsus pordi kohta	30 W
Auto MDI/MDI-X	✓	Toide üle võrgu (PoE) võimsusühikuid kokku	65 W
Automaatne ühildumine	✓	Töötingimused	
Automaatse MAC-aadressi tuvastamise tugi	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Automaatse MAC-aadressi aegumise tugi	✓	Hoiustamistemperatuur (T-T)	-40 - 70 °C
Andmeedastus		Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Lülitusvõime *	10 Gbit/s	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Edastamise kiirus	7,44 Mpps	Soojuse hajumine	253,16 BTU/h
MAC-aadresside tabel *	2000 sisestust	Kaal ja mõõtmed	
Ladusta-ja-edasta	✓	Laius	99,8 mm
Hiielkaadrite	16000	Sügavus	98 mm
Turvalisus		Kõrgus	25 mm
IGMP-jälgimine	✓	Pakendi andmed	
Disain		Kasutusjuhend	✓
Toote värv	Must	Pakendi tüüp	Karp
LED-indikaatorid	✓		
Sertifikaat	CE, FCC, RoHS		



4895252504552

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date