



## TP-Link Omada ER7212PC juhtmega ruuter Gigabit Ethernet Must



**Brand :** TP-Link

**Product family:** Omada

**Product code:** ER7212PC

**Product name :** ER7212PC

TP-Link Omada ER7212PC. Võrgustandardid: IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Ethernet-liidese tüüp: Gigabit Ethernet, Kaabeldustechnoloogia: 10/100/1000Base-T(X). Toetatud protokollid: TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, SNMP. NAT-funktsionaalsus: Multi-Net NAT; Virtual Server; NAT-DMZ; FTP/H.323/SIP/IPSec/PPTP ALG; UPnP;. Protsessori sagedus: 1200 MHz, Väikmälu: 4096 MB, Sisemälu: 1024 MB. Toote värv: Must, Korpuse materjal: Metall

WAN-ühendus		Turvalisus	
Ethernet WAN *	✓		
DSL WAN *	✗	NAT-funktsionaalsus	Multi-Net NAT; Virtual Server; NAT-DMZ; FTP/H.323/SIP/IPSec/PPTP ALG; UPnP;
SIM kaardi ava *	✗		
3G/4G USB modemi ühilduvus *	✗		
SFP WAN *	✓		
Võrgustumine		Funktsioonid	
Võrgustandardid *	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Sisesehitatud protsessor	✓
Ethernet-liidese tüüp *	Gigabit Ethernet	Protsessori sagedus	1200 MHz
Kaabeldustechnoloogia	10/100/1000Base-T(X)	Väikmälu	4096 MB
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s	Sisemälu	1024 MB
Staatiline ruutimine	✓	Sisemälu tüüp	DDR3
VLAN-i tugi	✓	Sertifikaat	CE, FCC, RoHS
Portide suunamine	✓		
Juhtimisfunktsioonid		Disain	
Universaalne Plug and Play (UPnP)	✓	Toote värv *	Must
Lähtestusnupp	✓	Korpuse materjal	Metall
Pesad & liidesed		LED-indikaatorid	✓
Ethernet LAN (RJ-45) pordid *	10	Võimsus	
Toide üle võrgu (PoE) pesade arv	8	Väljundpinge	53.5 V
Kombineeritud SFP-pesade arv	2	Väljundvool	2,43 A
DC-pistik	✓	Power over Ethernet tugi	✓
Protokollid		Töötingimused	
DHCP-klient *	✓	Kasutamistemperatuur (T-T)	0 - 45 °C
DHCP-server *	✓	Hoiustamistemperatuur (T-T)	-40 - 70 °C
Toetatud protokollid	TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, SNMP	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Turvalisus		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
URL-i filtreerimine	✓	Kaal ja mõõtmed	
Pääsuloend (ACL)	✓	Laius	226 mm
		Sügavus	131 mm
		Kõrgus	35 mm
		Pakendi andmed	
		AC-adapter kaasa arvatud	✓
		Juhend	✓
		Pakendi laius	227 mm
		Pakendi sügavus	374 mm
		Pakendi kõrgus	73 mm
		Pakendi kaal	1,92 kg



4897098688724



4897098688717



0840030708718



840030708718

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.