



TP-Link TL-MR105 juhtmevaba ruuter Kiire Ethernet Üks sagedusala (2,4 GHz) 4G Valge

Brand : TP-Link

Product code: TL-MR105

Product name : TL-MR105

TP-Link TL-MR105. WAN-ühenduse tüüp: RJ-45. Wi-Fi laineala: Üks sagedusala (2,4 GHz), Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN edastuskiirus (max): 300 Mbit/s. Ethernet LAN-liidese tüüp: Kiire Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100 Mbit/s. Mobiilsidevõrgu põlvkond: 4G, 3G-standardid: DC-HSPA+, HSDPA, HSPA, UMTS, 4G-standardid: LTE-TDD & LTE-FDD. Turvaalgoritmid: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, Tulemüür: IPv4 SPI Firewall



WAN-ühendus		Turvalisus	
Ethernet WAN *	✓	Tulemüür	✓
SIM kaardi ava *	✓	Tulemüür	IPv4 SPI Firewall
WAN-ühenduse tüüp	RJ-45	Külalise juurdepääs	✓
Juhtmevaba LAN-i omadused		DMZ-tugi	✓
Wi-Fi laineala *	Üks sagedusala (2,4 GHz)	Protokollid	
Wi-Fi standard *	Wi-Fi 4 (802.11n)	DHCP-klient	✓
WLAN edastuskiirus (max) *	300 Mbit/s	DHCP-server	✓
WiFi-standardid	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Universaalne Plug and Play (UPnP)	✓
WLAN edastuskiirus (esimene laineala)	300 Mbit/s	Disain	
Võrgustumine		Toote värv	Valge
Ethernet LAN *	✓	Toote tüüp *	Laua peale asetatav ruuter
Ethernet LAN-liidese tüüp *	Kiire Ethernet	Pakendi sisu	
Ethernet LAN-i andmeedastuskiirused	10,100 Mbit/s	Kaablid kaasa arvatud	LAN (RJ-45)
Portide suunamine	✓	Kiirpaigaldusjuhend	✓
Pordi aktiveerimine	✓	Jätkusuutlikkus	
Dünaamiline DNS (DDNS)	✓	Jätkusuutlikkuse järgimine	✓
Külalisvõrkude arv (2,4 GHz)	1	Antenn	
Mobiilivõrk		Antenni kujundus *	Sisemodem
Mobiilsidevõrgu põlvkond	4G	Võimsus	
3G-standardid	DC-HSPA+, HSDPA, HSPA, UMTS	Toiteallika tüüp *	DC (alalisvool)
4G-standardid	LTE-TDD & LTE-FDD	Töötingimused	
Toetatud 4G-ribad	800,850,900,1800,2100,2300,2500,2600 MHz	Kasutamistemperatuur (T-T)	0 - 40 °C
SIM-kaardi tüüp	NanoSIM	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Pesad & liidesed		Suhteline õhuniiskus (H-H) hoiustamisel	5 - 90 protsenti
Ethernet LAN (RJ-45) pordid *	2		

Pesad & liidesed		Kaal ja mõõtmed	
USB port *	✘	Laius	174 mm
DC-pistik	✔	Sügavus	130 mm
Juhtimisfunktsioonid		Kõrgus	60 mm
Lähtestusnupp	✔	Pakendi andmed	
WPS-nupp	✔	Pakendi tüüp	Karp
Turvalisus		Tehnilised andmed	
Turvaalgoritmid	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Vastavussertifikaadid	CE, RoHS



4895252503388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-AUG-2024. Prints or copies of Information are only valid on the printed Publication date