

ASUS ExpertWiFi EBP15 Juhitav Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Valge

Brand : ASUS

Product code: 90IG08D0-MO3B00

Product name : ExpertWiFi EBP15



ASUS ExpertWiFi EBP15. Lüliti tüüp: Juhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 5. MAC-aadresside tabel: 8000 sisestust. Võrgustandardid: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE.... Alalisvoolu sisendpinge: 54 V. Toitepistik: Alaldi sisendi pesa. Power over Ethernet tugi

Juhtimisfunktsioonid		Võimsus	
Lüliti tüüp *	Juhitav	AC-sisendpinge	100 - 240 V
Teenusekvaliteedi (QoS) tugi	✓	AC-sisendsagedus	50/60 Hz
Veebipõhine haldus	✓	Alalisvoolu sisendpinge	54 V
Pesad & liidesed		Sisendvool	1.25 A
RJ-45 Etherneti ühenduse pesade arv *	5	Sisendpinge	54 V
RJ-45 Etherneti ühenduse pesade tüüp *	Gigabit Ethernet (10/100/1000)	Internet elektrivõrgu kaudu (PoE)	
Toitepistik	Alaldi sisendi pesa	Power over Ethernet tugi *	✓
Võrgustumine		Toide üle võrgu (PoE) pesade arv	4
Võrgustandardid *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Toide üle võrgu (PoE) võimsus pordi kohta	30 W
10G-tugi *	✗	Toide üle võrgu (PoE) võimsusühikuid kokku	60 W
Pordipeegeldus	✓	Töötingimused	
Auto MDI/MDI-X	✓	Kasutamistemperatuur (T-T)	0 - 40 °C
Automaatne ühildumine	✓	Hoiustamistemperatuur (T-T)	-20 - 70 °C
Andmeedastus		Suhteline õhuniiskus kasutamisel (H-H)	10 - 95 protsenti
MAC-aadresside tabel *	8000 sisestust	Suhteline õhuniiskus (H-H) hoiustamisel	5 - 95 protsenti
Paketi puhvermälu	4 MB	Kaal ja mõõtmed	
Turvalisus		Laius	121 mm
IGMP-jälgimine	✓	Sügavus	75 mm
Turvaalgoritmid	SSL/TLS	Kõrgus	26 mm
Tsükli kaitse	✓	Kaal	248 g
Protokollid		Pakendi andmed	
Toetatud võrguprotokollid	IPv4	Kaablid kaasa arvatud	LAN (RJ-45)
Disain		Kiirstardi juhend	✓
Toote värv	Valge	AC-adapter kaasa arvatud	✓
LED-indikaatorid	Tegevus, Link, Internet elektrivõrgu kaudu (PoE), Võimsus, Kiirus	Pakendi laius	231 mm
		Pakendi sügavus	211 mm
		Pakendi kõrgus	97 mm
		Pakendi kaal	1,1 kg

Toimimine

Ülendatav püsivara ✓

Võimsus

Toiteallikas * DC (alalisvool)

Kaasas toiteplokk * ✗



4711387093986

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.