



LG 86TR3DK Interaktiivne tahvel 2,18 m (86") 3840 x 2160 pikslit Puutetundlik ekraan Must


Brand : LG

Product code: 86TR3DK-B.YUEQ

Product name : 86TR3DK



LG 86TR3DK. Ekraani diagonaal: 2,18 m (86"), Ekraani heledus: 390 cd/m², Ekraani resolutsioon: 3840 x 2160 pikslit. RAM-i maht: 32 GB, Graafikaadapter: Mali-G52 MP2. Kõlarite võimsus: 15 W. Kuvasuhe: 16:9. Wi-Fi standard: Wi-Fi 6 (802.11ax), WiFi-standardid: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s



Ekraan		Pesad & liidesed	
Ekraani diagonaal *	2,18 m (86")	USB 3.2 Gen 1 (3.1 Gen 1) A-tüüpi portide hulk	1
Ekraani heledus	390 cd/m ²	USB 2.0 portide arv	1
Ekraani resolutsioon	3840 x 2160 pikslit	HDMI-portide arv	3
HD tüüp	4K Ultra HD	Ethernet LAN (RJ-45) pordid	2
Paneeli tüüp	IPS	VGA (D-Sub) portide arv	1
Kontrastsustase (tüüpiline)	1200:1	Sisendkanal	✓
Kontrasti suhe (dünaamiline)	50000:1	Väljundkanal	✓
Reaktsiooniaeg	8 ms	OPS ava	1
Maksimaalne värskendussagedus	60 Hz	S/DPDIF-väljund	✓
Puutetundlik ekraan *	✓	RS-232 portide arv	1
Vaatenurk, horisontaalne	178°	Ergonoomika	
Vaatenurk, vertikaalne	178°	Toote värv	Must
Värvigamma	72 protsenti	VESA paigaldamine	✓
Arvutisüsteem		VESA-paigaldusliidesed	800 x 600 mm
RAM-i maht	32 GB	Võimsus	
Graafikaadapter	Mali-G52 MP2	Elektritarbimine (max)	580 W
Audio		Võimsustarve (tüüpiline)	385 W
Sisseehitatud kõlar(id) *	✓	Võimsustarve (väljalülitatud)	0,5 W
Sisseehitatud kõlarite arv	2	AC-sisendpinge	100 - 240 V
Kõlarite võimsus	15 W	AC-sisendsagedus	50 - 60 Hz
Projektor		Töötingimused	
Sisseehitatud projektor *	✗	Kasutamistemperatuur (T-T)	0 - 40 °C
Kuvasuhe	16:9	Suhteline õhuniiskus kasutamisel (H-H)	10 - 90 protsenti
Võrgustumine		Kaal ja mõõtmed	
WiFi	✓	Laius *	1957 mm
Wi-Fi standard	Wi-Fi 6 (802.11ax)	Sügavus	1160 mm
WiFi-standardid	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Kõrgus *	100 mm
Bluetooth	✓	Kaal	58,6 kg
Bluetoothi versioon	5.0	Pakendi andmed	
Ethernet LAN	✓	Pakendi laius	2110 mm
Ethernet LAN-i andmeedastuskiirused	10,100,1000 Mbit/s	Pakendi sügavus	1283 mm
		Pakendi kõrgus	225 mm

Pesad & liidesed

HDCP	✓
HDCP versioon	2.2

Pakendi andmed

Pakendi kaal	75,9 kg
--------------	---------

Jätkusuutlikkus

Jätkusuutlikkuse sertifikaadid	ENERGY STAR
--------------------------------	-------------

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-NOV-2024. Prints or copies of Information are only valid on the printed Publication date