

APC SMT750IC puhvertoiteallikas (UPS) Liini-interaktiivne 0,75 kVA 500 W 6 vahelduvvoolu kontakt

Brand : APC Product code: SMT750IC

Product name: SMT750IC

APC SMT750IC. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 0,75 kVA, Väljundvõimsus: 500 W. AC-väljundi tüüp: C13 pistikut, Elektripistik: C14 pistikut, AC-väljundite arv: 6 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Tüübipärane varundamisaeg täiskoormusega: 4,6 min, Tüübipärane varundamisaeg poole koormusega: 15,8 min. Toote kuju: Tower, Toote värv: Must, Kaabli pikkus: 1,83 m. Laius: 138 mm, Sügavus: 358 mm, Kõrgus: 157 mm





| Features | | Battery | |
|--|---|---|--|
| UPS topology * | Line-Interactive | Cold start | ✓ |
| Output power capacity * Output power * | 0.75 kVA 500 W | Design | |
| Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Automatic Voltage Regulation (AVF | Sine 151 V x) * 302 V 50/60 Hz nin) 220 V nax) 240 V on (AVR) ✓ 540 J | Form factor * Cable length Product colour * Display type LED indicators Certification | Tower 1.83 m Black LCD Status CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOLI |
| Surge energy rating | | Operational conditions | 732, 112, 13, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, |
| Efficiency Noise level Audible alarm(s) Auto-restart | 98% 40 dB • | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) | 0 - 40 °C -15 - 45 °C 5 - 95% 0 - 95% |
| Ports & interfaces | | Operating altitude | 0 - 3000 m |
| AC outlet types Power plug AC outlets quantity Number of output IEC jumpers | C13 coupler C14 coupler 6 AC outlet(s) 2 | Non-operating altitude Technical details Sustainability certificates Compliance certificates | 0 - 15000 m Green Premium RoHS |
| USB port | ✓ | Weight & dimensions | |
| Ethernet LAN (RJ-45) ports SmartSlot | 1 | Width Depth | 138 mm 358 mm |
| Battery | | Height | 157 mm |
| Battery technology Typical backup time at full load Typical backup time at half load | Sealed Lead Acid (VRLA) 4.6 min 15.8 min | Weight Package width Package depth | 13.2 kg 278 mm 499 mm |

| Battery | | Weight & dimensions | |
|---|-----------|--|---------------------------|
| Battery life (max) | 5 year(s) | Package height | 301 mm |
| Battery recharge time | 3 h | Package weight | 14.2 kg |
| Hot-swap battery Automatic battery test | * | Packaging data | |
| | | Cables included | USB cable |
| | | Manual | ✓ |
| | | Quick installation guide | ✓ |
| | | Bundled software | Powershute Serial Edition |
| | | Logistics data | |
| | | Products per pallet Harmonized System (HS) code | 24 pc(s) 85078000 |





731304340317

0731304340317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.