



APC Back-UPS puhvertoiteallikas (UPS) Liini-interaktiivne 0,5 kVA
300 W 3 vahelduvvoolu kontakt

Brand : APC

Product code: BX500MI


Product name : Back-UPS

APC Back-UPS. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 0,5 kVA, Väljundvõimsus: 300 W. AC-väljundi tüüp: C13 pistikut, Elektripistik: C14 pistikut, AC-väljundite arv: 3 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Aku pinge: 12 V, Aku kasutusiga (max): 5 aasta(t). Toote kuju: Tower, Toote värv: Must, Kaabli pikkus: 1,5 m. Laius: 98 mm, Sügavus: 310 mm, Kõrgus: 138 mm



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	0.5 kVA	Design	
Output power *	300 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.5 m
Input operation voltage (min) *	140 V	Product colour *	Black
Input operation voltage (max) *	300 V	LED indicators	Battery replacement
Input frequency *	50/60 Hz	International Protection (IP) code	IP20
Output frequency	50/60 Hz	Certification	CE, EAC, EN/IEC 62040-1
Automatic Voltage Regulation (AVR)	✓	Operational conditions	
Surge energy rating	273 J	Operating temperature (T-T)	0 - 40 °C
Efficiency	96.1%	Storage temperature (T-T)	-15 - 40 °C
Input power factor	0.63	Operating relative humidity (H-H)	0 - 95%
Noise level	40 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection	✓	Operating altitude	0 - 3000 m
Audible alarm(s)	✓	Non-operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Low battery alarm	Technical details	
Ports & interfaces		Compliance certificates	RoHS
AC outlet types	C13 coupler	Weight & dimensions	
Power plug	C14 coupler	Width	98 mm
AC outlets quantity	3 AC outlet(s)	Depth	310 mm
Number of output IEC jumpers	1	Height	138 mm
Ethernet LAN (RJ-45) ports	2	Weight	4.2 kg
Cabling technology	10/100/1000Base-T(X)	Package width	142 mm
Battery		Package depth	346 mm
Battery technology	Sealed Lead Acid (VRLA)	Package height	222 mm
Battery voltage	12 V	Package weight	4.5 kg
Battery life (max)	5 year(s)		

Battery		Logistics data	
Battery recharge time	8 h	Harmonized System (HS) code	85078000



0731304435648



731304435648

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.