



## APC Back-UPS puhvertoiteallikas (UPS) Ooteseisund (võrgust väljas) 0,5 kVA 300 W 4 vahelduvvoolu kontakt

Brand : APC

Product code: BK500EI

Product name : Back-UPS

APC Back-UPS. Puhvertoiteallika topoloogia: Ooteseisund (võrgust väljas), Väljundvõimsuse potentsiaal: 0,5 kVA, Väljundvõimsus: 300 W. AC-väljundi tüüp: C13 pistikut, Elektripistik: C14 pistikut, AC-väljundite arv: 4 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Aku mahutavus: 7 Ah, Aku vastupidavus: 83 VAh. Toote kuju: Tower, Toote värv: Beež, Kaabli pikkus: 1,83 m. Laius: 91 mm, Sügavus: 284 mm, Kõrgus: 165 mm



Features		Design	
UPS topology *	Standby (Offline)	Product colour *	Beige
Output power capacity *	0.5 kVA	LED indicators	Battery replacement
Output power *	300 W	Certification	C-tick, CE, EN 50091-1, EN 50091-2, GOST, VDE, REACH
Waveform *	Sine	Operational conditions	
Input operation voltage (min) *	160 V	Operating temperature (T-T)	0 - 40 °C
Input operation voltage (max) *	300 V	Storage temperature (T-T)	-15 - 45 °C
Input frequency *	50/60 Hz	Operating relative humidity (H-H)	0 - 95%
Output frequency regulation	47 - 63 Hz	Storage relative humidity (H-H)	0 - 95%
Surge energy rating	310 J	Operating altitude	0 - 3000 m
Hold time (min)	6 ms	Non-operating altitude	0 - 15000 m
Hold time (max)	10 ms	Technical details	
Efficiency	99%	Sustainability certificates	ENERGY STAR, Green Premium
Noise level	40 dB	Compliance certificates	RoHS
Surge protection	✓	Weight & dimensions	
Surge protection features	Digital Subscriber Line (DSL), Fax, Modem, Telephone	Width	91 mm
Power protection features	Overload	Depth	284 mm
Audible alarm(s)	✓	Height	165 mm
Audible alarm modes	Low battery alarm, Overload alarm	Weight	6.32 kg
Ports & interfaces		Package width	241 mm
AC outlet types	C13 coupler	Package depth	368 mm
Power plug	C14 coupler	Package height	178 mm
AC outlets quantity	4 AC outlet(s)	Package weight	7.05 kg
Number of output IEC jumpers	2		

Ports & interfaces		Packaging data	
USB port	✓	Cables included	Phone (RJ-11), USB cable
Battery		Quick installation guide	✓
Battery technology	Sealed Lead Acid (VRLA)	Warranty card	✓
Battery capacity	7 Ah	Software CD	✓
Battery capacity	83 VAh	Bundled software	PowerChute Personal Edition
Battery voltage	12 V	Logistics data	
Typical backup time at full load	3.8 min	Products per pallet	48 pc(s)
Typical backup time at half load	13.8 min	Harmonized System (HS) code	85078000
Battery life (max)	6 year(s)	Products per master (outer) case	1 pc(s)
Battery recharge time	8 h	Other features	
Automatic battery test	✓	Nominal output voltage	230 V
Design		Nominal input voltage	230 V
Form factor *	Tower	Filtering	✓
Cable length	1.83 m	Packaging content	Detachable 1.2m IEC power cord Detachable 1.8 m IEC power cord



0731304016359



731304016359

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.