



APC SMT1500IC puhvertoiteallikas (UPS) Liini-interaktiivne 1,5 kVA 1000 W 8 vahelduvvoolu kontakt

Brand : APC

Product code: SMT1500IC

Product name : SMT1500IC

APC SMT1500IC. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 1,5 kVA, Väljundvõimsus: 1000 W. AC-väljundi tüüp: C13 pistikut, IEC Jumpers, Elektripistik: C14 pistikut, AC-väljundite arv: 8 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Aku kasutusiga (max): 5 aasta(t), Aku laadimisaeg: 3 h. Toote kuju: Mini Tower, Toote värv: Must, Kaabli pikkus: 1,83 m. Laius: 171 mm, Sügavus: 439 mm, Kõrgus: 219 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	1.5 kVA	Hot-swap battery	✓
Output power *	1000 W	Automatic battery test	✓
Waveform *	Sine	Cold start	✓
Input operation voltage (min) *	151 V		
Input operation voltage (max) *	302 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	459 J		
Output voltage Total Harmonic Distortion (THD)	5%		
Noise level	45 dB		
Surge protection	✓		
Audible alarm(s)	✓		
Web-based management	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Auto-restart	✓		
Temperature voltage compensation	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, IEC Jumpers	Form factor *	Mini Tower
Power plug	C14 coupler	Cable length	1.83 m
AC outlets quantity	8 AC outlet(s)	Product colour *	Black
		Display type	LCD
		LED indicators	✓
		Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-15 - 45 °C
		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	Green Premium
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	171 mm
		Depth	439 mm

Ports & interfaces		Weight & dimensions	
USB port	✓	Height	219 mm
USB 2.0 ports quantity	1	Weight	24.1 kg
Serial interface	✓	Package width	328 mm
Serial interface type	RS-232	Package depth	595 mm
Serial ports quantity	1	Package height	376 mm
Ethernet LAN (RJ-45) ports	1	Package weight	27.2 kg
SmartSlot	✓	Packaging data	
Battery		Cables included	RS-232, USB cable
Battery technology	Sealed Lead Acid (VRLA)	Quick installation guide	✓
Battery life (max)	5 year(s)	Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	12 pc(s)
		Harmonized System (HS) code	85078000



0731304332992



731304332992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.