

## DELL E Series E2225H PC lamekuvar 54,5 cm (21.4") 1920 x 1080 pikslit Full HD LCD Must

Brand : DELL Product family: E Series Product code: DELL-E2225H

**Product name :** E2225H

DELL E Series E2225H. Ekraani diagonaal: 54,5 cm (21.4"), Ekraani resolutsioon:  $1920 \times 1080$  pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 8 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne:  $178^\circ$ , Vaatenurk, vertikaalne:  $178^\circ$ . VESA paigaldamine. Toote värv: Must





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology *	54.5 cm (21.4") 1920 x 1080 pixels Full HD 16:9 LCD	Tilt adjustment Tilt angle range On Screen Display (OSD) Plug and Play LED indicators	✓ -5 - 21° ✓
Panel type * LED backlight Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen Screen shape * Supported graphics resolutions Supported video modes	VA  Edge LED  X  250 cd/m²  8 ms  Flat  640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1600 x 900, 1920 x 1080 (HD 1080) 480p, 576p, 720p, 1080p	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Power supply type Energy efficiency scale	D Not available  12 kWh  11.9 W 0.3 W 19 W 0.3 W 100 - 240 V 50/60 Hz Internal A to G
Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Horizontal scan range	3000:1 75 Hz 178° 178° 16.7 million colours 5 ms 0.2493 x 0.241 mm 103 ppi 30 - 84 kHz	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Vertical scan range Viewable size, horizontal Viewable size, vertical Display diagonal (metric)	50 - 76 Hz 47.9 cm 26 cm 544.85 cm	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand)	504.3 mm 171 mm 384.2 mm 2.67 kg

Display		Weight & dimensions	
High Dynamic Range (HDR) supported Surface hardness NTSC coverage (typical)	<b>X</b> 3H 83%	Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	504.3 mm 49.6 mm 295.4 mm 2.34 kg
Performance		Bezel width (side)	1.28 cm
NVIDIA G-SYNC * AMD FreeSync *	× ×	Bezel width (top) Bezel width (bottom)	1.28 cm 1.69 cm
Flicker-free technology	✓	Packaging data	
Low Blue Light technology	✓	Package weight	4.18 kg
Multimedia		Packaging content	
Built-in speaker(s) * Built-in camera *  Design	× ×	Stand included Cables included Quick start guide DisplayPort cable length	✓ AC, DisplayPort, VGA ✓ 1.8 m
Market positioning * Product colour * Front bezel colour Detachable stand	Home Black Black	Sustainability	
		Sustainability certificates Doesn't contain	ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR
Feet colour	Black	Carbon footprint	
Ports & interfaces		Total carbon footprint (kg of CO2e)	124
Built-in USB hub * VGA (D-Sub) ports quantity HDMI * DisplayPorts quantity DisplayPort version Headphone out * HDCP HDCP version	x 1 x 1 1.2 x 1.4	Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version	56 8 59 1 65 GaBi version 1, 2024
Network		Other features	
Wi-Fi	X	(cdm) Box content	C13 Power Cord 220V 1.8M
Ergonomics		Compliance certificates	RoHS
VESA mounting * Panel mounting interface Wall mountable Cable lock slot * Cable lock slot type Height adjustment *	✓ 100 x 100 mm ✓ ✓ Kensington		
Pivot	×		

Swivelling

X

