## **NOC**

## AOC 24B3HMA2 PC lamekuvar 60,5 cm (23.8") 1920 x 1080 pikslit Full HD LED Must

Brand : AOC Product code: 24B3HMA2

**Product name:** 24B3HMA2

AOC 24B3HMA2. Ekraani diagonaal: 60,5 cm (23.8"), Ekraani resolutsioon: 1920 x 1080 pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LED, Reaktsiooniaeg: 4 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud kõlar(id). VESA paigaldamine. Toote värv: Must





Display		Design	
	60 F cm (22 0")	Front bezel colour	Black
Display diagonal * Display resolution *	60.5 cm (23.8") 1920 x 1080 pixels		
HD type *	Full HD	Detachable stand	<b>✓</b>
Native aspect ratio *	16:9	Ports & interfaces	
Display technology *	LED	Built-in USB hub *	×
Panel type *	VA	VGA (D-Sub) ports quantity	1
LED backlight	<b>√</b>	HDMI *	<b>✓</b>
Backlight type	W-LED	HDMI ports quantity	1
Touchscreen *	×	HDMI version	1.4
	250 cd/m <sup>2</sup>	Audio input	<b>✓</b>
Display brightness (typical) Response time *	4 ms	Audio output	/
Anti-glare screen	4 III3 ✓	HDCP	1
Screen shape *	Flat	HDCP version	1.4
Aspect ratio	16:9	AC (power) in	√
Contrast ratio (typical) *	4000:1	·	•
	<del>1</del> 000.1		
	20000000:1	Ergonomics	
Contrast ratio (dynamic)	20000000:1 100 Hz	VESA mounting *	<b>✓</b>
Contrast ratio (dynamic) Maximum refresh rate *	20000000:1 100 Hz 178°	-	✓ 100 x 100 mm
Contrast ratio (dynamic)	100 Hz	VESA mounting *	
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal	100 Hz 178°	VESA mounting * Panel mounting interface	100 x 100 mm
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical	100 Hz 178° 178°	VESA mounting * Panel mounting interface Cable lock slot *	100 x 100 mm ✓
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours *	100 Hz 178° 178° 16.7 million colours	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type	100 x 100 mm  ✓ Kensington
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast)	100 Hz 178° 178° 16.7 million colours 1 ms	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range	100 x 100 mm  ✓  Kensington -5 - 23°
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Digital horizontal frequency	100 Hz 178° 178° 16.7 million colours 1 ms 0.2745 x 0.2745 mm 93 ppi 30 - 115 kHz	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range LED indicators  Power	100 x 100 mm  ✓  Kensington -5 - 23°
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Digital horizontal frequency Digital vertical frequency	100 Hz 178° 178° 16.7 million colours 1 ms 0.2745 x 0.2745 mm 93 ppi 30 - 115 kHz 48 - 100 Hz	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range LED indicators	100 x 100 mm  ✓  Kensington -5 - 23°  Status
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Digital horizontal frequency Digital vertical frequency Display diagonal (metric)	100 Hz 178° 178° 16.7 million colours 1 ms 0.2745 x 0.2745 mm 93 ppi 30 - 115 kHz 48 - 100 Hz 60.5 cm	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range LED indicators  Power Power consumption (typical) *	100 x 100 mm  ✓  Kensington -5 - 23°  Status
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Digital horizontal frequency Digital vertical frequency Display diagonal (metric) Haze rate	100 Hz 178° 16.7 million colours 1 ms 0.2745 x 0.2745 mm 93 ppi 30 - 115 kHz 48 - 100 Hz 60.5 cm 25%	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range LED indicators  Power Power consumption (typical) * Power consumption (standby) *	100 x 100 mm  ✓  Kensington -5 - 23°  Status  23 W 0.5 W
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Digital horizontal frequency Digital vertical frequency Display diagonal (metric)	100 Hz 178° 178° 16.7 million colours 1 ms 0.2745 x 0.2745 mm 93 ppi 30 - 115 kHz 48 - 100 Hz 60.5 cm	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range LED indicators  Power  Power consumption (typical) * Power consumption (standby) * Power consumption (max)	100 x 100 mm  ✓  Kensington -5 - 23°  Status  23 W 0.5 W 35 W
Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density Digital horizontal frequency Digital vertical frequency Display diagonal (metric) Haze rate	100 Hz 178° 16.7 million colours 1 ms 0.2745 x 0.2745 mm 93 ppi 30 - 115 kHz 48 - 100 Hz 60.5 cm 25%	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Tilt angle range LED indicators  Power  Power consumption (typical) * Power consumption (max) Power consumption (off)	100 x 100 mm  ✓  Kensington -5 - 23°  Status  23 W 0.5 W 35 W 0.3 W

Performance		Operational conditions	
Flicker-free technology	<b>✓</b>	Operating temperature (T-T)	0 - 40 °C
Low Blue Light technology	<b>✓</b>	Storage temperature (T-T)	-25 - 55 °C
Multimedia		Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	10 - 85% 5 - 93% 0 - 5000 m
Number of speakers	2		
RMS rated power	2 W	Non-operating altitude	0 - 12192 m
Built-in speaker(s) *	✓	Packaging content	
Built-in camera *	X	Cables included	AC, HDMI
Design		HDMI cable length	1.5 m
Market positioning *	Home		
Product colour *	Black		



4038986141529

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.