

DELL E Series E2425H PC lamekuvar 60,5 cm (23.8") 1920 x 1080 pikslit Full HD LCD Must

Brand : DELL

Product family: E Series

Product code: DELL-E2425H

Product name : E2425H

DELL E Series E2425H. Ekraani diagonaal: 60,5 cm (23.8"), Ekraani resolutsioon: 1920 x 1080 pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 8 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. VESA paigaldamine. Toote värv: Must





Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Tilt angle range	-5 - 21°
Display resolution *	1920 x 1080 pixels	On Screen Display (OSD)	✓ [−]
HD type *	Full HD		
Native aspect ratio *	16:9	Plug and Play	
Display technology *	LCD	LED indicators	1
Panel type *	VA	Power	
LED backlight	1	Energy efficiency class (SDR) *	D
Backlight type	Edge LED	Energy efficiency class (HDR) *	Not available
Touchscreen *	×	Energy consumption (SDR) per 1000	13 kWh
Display brightness (typical)	250 cd/m ²	hours *	
Response time *	8 ms	Power consumption (typical) *	13.3 W
Anti-glare screen	v	Power consumption (standby) *	0.3 W
5		Power consumption (max)	22 W
Screen shape *	Flat	Power consumption (off)	0.3 W
	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA),	AC input voltage	100 - 240 V
Supported graphics resolutions	1152 x 864 (XGA+), 1280 x 1024	AC input frequency	50/60 Hz
	(SXGA), 1280 x 720 (HD 720), 1600	Power supply type	Internal
	x 900, 1920 x 1080 (HD 1080)	Energy efficiency scale	A to G
Supported video modes	480p, 576p, 720p, 1080p	Operational conditions	
Contrast ratio (typical) *	3000:1	Operating temperature (T-T)	0 - 40 °C
Maximum refresh rate *	75 Hz		
Viewing angle, horizontal	178°	Storage temperature (T-T)	-20 - 60 °C
Viewing angle, vertical	178°	Operating relative humidity (H-H)	10 - 80%
Display number of colours *	16.7 million colours	Storage relative humidity (H-H)	5 - 90%
Response time (fast)	5 ms	Operating altitude	0 - 5000 m
Pixel pitch	0.2745 x 0.2745 mm	Non-operating altitude	5000 - 12192 m
Pixel density	93 ppi	Weight & dimensions	
Horizontal scan range	30 - 84 kHz	Width (with stand)	552.6 mm
Vertical scan range	50 - 76 Hz	Depth (with stand)	171 mm
Viewable size, horizontal	52.7 cm	Height (with stand)	420.4 mm
Viewable size, vertical	29.6 cm	Weight (with stand)	3.49 kg
Display diagonal (metric)	604.7 cm	Width (without stand)	552.6 mm
		Depth (without stand)	49.7 mm
		Depth (Michoue Stand)	

Display		Weight & dimensions	
High Dynamic Range (HDR)	×	Height (without stand)	331.6 mm
supported Surface hardness	ЗН	Weight (without stand)	3.16 kg
NTSC coverage (typical)	83%	Bezel width (side)	1.28 cm
Performance		Bezel width (top) Bezel width (bottom)	1.28 cm 1.69 cm
NVIDIA G-SYNC *			1.05 cm
	X	Packaging data	F 47 hr
AMD FreeSync *	×	Package weight VGA cable length	5.47 kg 1.5 m
Flicker-free technology			1.5 m
Low Blue Light technology	•	Packaging content	-
Multimedia		Stand included	
Built-in speaker(s) *	×	Cables included	AC, DisplayPort, VGA
Built-in camera *	×	Quick start guide	✓ 1.8 m
Design		DisplayPort cable length Power cable length	1.8 m 2 m
Market positioning *	Home	Sustainability	
Product colour *	Black		ENERCY STAR TOO
Front bezel colour	Black	Sustainability certificates Doesn't contain	ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR
Detachable stand	<i>✓</i>		Alsonic, Mercury, Tvo, Driv
Feet colour	Black	Carbon footprint	
Ports & interfaces		Total carbon footprint (kg of CO2e) Carbon emissions, manufacturing	143
Built-in USB hub *	×	(kg of CO2e)	64
VGA (D-Sub) ports quantity	1	Carbon emissions, logistics (kg of	10
HDMI *	×	CO2e)	
DisplayPorts quantity	1	Carbon emissions, energy usage (kg of CO2e)	65
DisplayPort version	1.2	Carbon emissions, end-of-life (kg of	3
Headphone out *	×	CO2e)	-
HDCP HDCP version	1.4	Total carbon emissions, w/o use phase (kg of CO2e)	78
	1.4	PAIA version	GaBi version 1, 2024
Network		Other features	
Wi-Fi	×	(cdm) Box content	C13 Power Cord 220V 2M
Ergonomics		Compliance certificates	RoHS
VESA mounting *	✓		
Panel mounting interface	100 x 100 mm		
Wall mountable	1		
Cable lock slot *	1		
Cable lock slot type	Kensington		
Height adjustment *	×		
Pivot	×		
Swivelling	×		
Tilt adjustment	 Image: A second s		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.