Imou Cruiser SE+ Ülepea IP süsteemiga turvakaamera Hooneväline 2560 x 1440 pikslit Lagi/sein

Brand : Imou

Product code: IPC-S41FEP-IMOU

Product name : Cruiser SE+

Imou Cruiser SE+. Tüüp: IP süsteemiga turvakaamera, Toetatud paigutus: Hooneväline, Ühenduvustehnoloogia: Juhtmega ühendatud & juhtmevaba. Kinnituse tüüp: Lagi/sein, Toote värv: Valge, Toote kuju: Ülepea. Objektiivi vaatenurk, horisontaalne: 79°, Objektiivi vaatenurk, vertikaalne: 44°, Objektiivi vaatenurk, diagonaalne: 94°. Anduri tüüp: CMOS, Optilise sensori suurus: 25,4 / 3 mm (1 / 3"). Digitaalne suum: 16x, Objektiivi läbimõõt: 3,6 mm

Performance

Type *	IP security camera
Placement supported *	Outdoor
Connectivity technology *	Wired & Wireless
Antenna type	External
Antennas quantity	2
Certification	FCC

Design

Form factor *	Dome
Mounting type *	Ceiling/wall
Product colour *	White
Housing material	Plastic
Protection features	Dust resistant, Waterproof
International Protection (IP) code	IP66
Weatherproof	✔

Camera

Camera pan control	✔
Camera tilt control	✔
Lens viewing angle, horizontal	79°
Lens viewing angle, vertical	44°
Lens viewing angle, diagonal	94°
Tilt angle range	0 - 90°
Pan range	0 - 355°

Image sensor

Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	✔
Sensor type *	CMOS

Lens system

Zoom capability	✔
Digital zoom	16x
Number of lenses *	1
Lens diameter	3.6 mm

Night vision

Night vision *	✔
Night vision distance	30 m

Video

Maximum resolution *	2560 x 1440 pixels
Total megapixels *	4 MP
Video compression formats	H.265
Frame rate	25 fps

Network

Supported network protocols	ONVIF
Wi-Fi *	✔
Wi-Fi standards	802.11g, 802.11b, Wi-Fi 4 (802.11n)
Bluetooth *	✘

Storage

Built-in HDD *	✘
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	256 GB

Ports & interfaces

Ethernet LAN (RJ-45) ports	1

Security

Siren noise level	110 dB
Video motion detection	✔
Alert notification type	Text alert message
Intelligent Video Surveillance (IVS) system features	Human detection
Configurable region	✔

Management features

Reset button	✔

Power

Power source type *	DC
Power consumption (typical)	6.2 W
DC output voltage	12
DC output current	1 A

Operational conditions

Operating temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%

System requirements

Mobile operating systems supported	Android, iOS

Weight & dimensions

Width	120.7 mm
Depth	136.2 mm
Height	183.3 mm
Weight	395 g

Sustainability

Sustainability compliance	✔
Compliance certificates	UKCA, CE

Packaging content

Number of cameras *	1

Audio		**Packaging content**	
Built-in speaker(s)	✔	Mounting brackets included	✔
Audio system	2-way	Screws included	✔
Built-in microphone	✔	Manual	✔
Network		AC adapter included	✔
Ethernet LAN *	✔	Anchors included	✔
Ethernet interface type	Fast Ethernet	Mounting template	✔
		Waterproof connector	✔

6971927236886