

TP-Link Deco X50-Outdoor Kaks sagedusala (2,4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Valge 2 Sisemodem

Brand : TP-Link Product code: DECOX500UTDOOR1P

Product name: Deco X50-Outdoor

TP-Link Deco X50-Outdoor. Toote värv: Valge, Antenni tüüp: Sisemodem, Toote tüüp: Võrguruuter. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 6 (802.11ax), WiFi-standardid: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Toetatud 4G-ribad: 700,800,850,900,1800,2100,2300,2500,2600 MHz. Võimsustarve (tüüpiline): 15,5 W, AC-sisendpinge: 100 - 240 V, Vooluadapteri sisendvõimsus: 0,5 A. Sertifikaat: CE, RoHS





Design		Features	
Product type Product colour * LED indicators Antenna type * Antennas quantity	Mesh router White Yes Internal 4 <30 dBm(2.4 GHz), <30 dBm(5	DHCP client DHCP server Universal Plug and Play (UPnP) MU-MIMO technology MIMO	* * * * *
Transmit power	GHz)	Ports & interfaces	
Reset button	1	Ethernet LAN (RJ-45) ports *	2
Wireless LAN features		Ethernet WAN	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Power	
Top Wi-Fi standard * Wi-Fi standards	Wi-Fi 6 (802.11ax) 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Power consumption (typical) AC input voltage AC adapter input current	15.5 W 100 - 240 V 0.5 A
WLAN data transfer rate (first band)	574 Mbit/s	AC input frequency	50 - 60 Hz
WLAN data transfer rate (second band)	2402 Mbit/s	Certificates	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11q, IEEE 802.11n	Certification Operational conditions	CE, RoHS
Security algorithms Number of guest networks (5 GHz) Number of guest networks (2.4 GHz)	WPA, WPA2, WPA3 1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-30 - 60 °C -40 - 70 °C 10 - 90% 5 - 90%
Point-to-point protocol over Ethernet (PPPoE)	✓	Weight & dimensions	
Dynamic IP	✓	Width	110 mm
Static IP	✓	Depth Height	121.3 mm
IGMP proxy	✓		215.5 mm
IGMP snooping	✓		

Wireless LAN features		Packaging content	
Tagged VLAN	✓	Number of products included	1 pc(s)
Dynamic DNS (DDNS)	✓	Number of units included	1 pc(s)
Guest access	✓	Ethernet cable	✓
Apps supported	TP-Link Deco	Quick installation guide	✓
Mobile network			
4G bands supported	700,800,850,900,1800,2100,2300,2500,2600 MHz		

