

DELL PowerEdge T360 server 480 GB Torn (4.5U) Intel Xeon E E-2414 2,6 GHz 16 GB DDR5-SDRAM 700 W

Brand : DELL **Product family:** PowerEdge **Product code:** EMEA_PET360SPL3

Product name: T360

DELL PowerEdge T360. Protsessori perekond: Intel Xeon E, Protsessori sagedus: 2,6 GHz, Protsessori mudel: E-2414. Sisemälu: 16 GB, Sisemälu tüüp: DDR5-SDRAM, Mälu (pesad x suurus): 1 x 16 GB. Salvestusmaht kokku: 480 GB. Ethernet LAN, Kaabeldustehnoloogia: 10/100/1000Base-T(X). Toiteallikas: 700 W, Üleliigse toite (RPS) tugi. Keretüüp: Torn (4.5U)





Processor		Design	
Processor manufacturer * Intel Processor family * Intel Xeon E Processor model * E-2414	Chassis type * Product colour Bezel	Tower (4.5U) Black ✔	
Processor frequency *	2.6 GHz	Performance	
Processor boost frequency Performance cores	4.5 GHz 4	Remote administration	iDRAC9 Basic 16G
Processor cores	4	Software	
Processor cache Number of processors installed Processor threads	12 MB 1 4	Operating system installed * Compatible operating systems *	X Canonical Ubuntu Server LTS Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux
Memory Internal memory *	16 GB	compariste operating systems	SUSE Linux Enterprise Server VMware ESXi
Internal memory type * DDR5-SDRAM		Power	
Buffered memory type Memory slots	Unregistered (unbuffered) 4x DIMM	Redundant power supply (RPS) support *	✓
ECC	✓	Power supply *	700 W
Memory clock speed Memory layout (slots x size)	4800 MHz 1 x 16 GB	Number of redundant power supplies supported	2
Maximum internal memory *	128 GB	Number of redundant power supplies installed	2
Storage		Operational conditions	
Total storage capacity * 480 GB Number of SSDs installed 1 SSD capacity 480 GB SSD interface SATA III SSD size 2.5"	Storage temperature (T-T) Storage relative humidity (H-H) Operating altitude Non-operating altitude	-40 - 65 °C 5 - 95% 0 - 2048 m 0 - 12000 m	
Supported SSD sizes	2.5" 3.5"	Certificates	
Number of SSDs supported	8	80 PLUS certification	80 PLUS Titanium
RAID support *	✓		

Storage		Carbon footprint	
Supported RAID controllers	PERC H355	Total carbon footprint (kg of CO2e)	1409
Hot-Plug support Internal drive bays	√ 8	Total carbon emissions, standard deviation (kg of CO2e)	1213
Drive writes per day (DWPD)	1	Carbon emissions, manufacturing (kg of CO2e)	296
Storage drive adapter included Storage drive adapter type	2 .5" - 3.5"	Carbon emissions, logistics (kg of CO2e)	155
Network		Carbon emissions, energy usage (kg of CO2e)	930
LAN controller Ethernet LAN	Broadcom 5720 ✓	Carbon emissions, end-of-life (kg of CO2e)	28
Cabling technology Ethernet interface type	10/100/1000Base-T(X) Gigabit Ethernet	Total carbon emissions, w/o use phase (kg of CO2e)	479
Ports & interfaces	3	PAIA version	1.4.0, 2024
	2	Weight & dimensions	
Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A	2 5 2	Width Depth Height	175 mm 581.1 mm 369.5 mm
ports quantity VGA (D-Sub) ports quantity	1	Technical details	309.3 111111
Serial ports quantity	1	Supported storage drives form	3.5"
Expansion slots		factor (internal)	J.J
PCI Express x4 slots	2	Other features	
		Data transfer rate Bytes per sector	6 Gbit/s 512

