

DELL PowerEdge T360 server 480 GB Torn (4.5U) Intel Xeon E E-2434 3,4 GHz 16 GB DDR5-SDRAM 700 W

Brand : DELL **Product family:** PowerEdge **Product code:** EMEA_PET360SPL2

Product name: T360

DELL PowerEdge T360. Protsessori perekond: Intel Xeon E, Protsessori sagedus: 3,4 GHz, Protsessori mudel: E-2434. Sisemälu: 16 GB, Sisemälu tüüp: DDR5-SDRAM, Mälu (pesad x suurus): 1 x 16 GB. Salvestusmaht kokku: 480 GB. Ethernet LAN, Kaabeldustehnoloogia: 10/100/1000Base-T(X). Toiteallikas: 700 W, Üleliigse toite (RPS) tugi. Keretüüp: Torn (4.5U)





Processor		Design	
Processor manufacturer * Processor family *	ocessor family * Intel Xeon E	Product colour Bezel	Black ✓
Processor model * Processor frequency *	E-2434 3.4 GHz	Performance	
Processor boost frequency	•	Remote administration	iDRAC9 Basic
Performance cores	4	Software	
Processor cores 4 Processor cache 12 MB Number of processors installed 1 Thermal Design Power (TDP) 55 W Processor threads 8		Operating system installed *	×
		Power	
	Redundant power supply (RPS) support *	✓	
	Ü	Power supply *	700 W
Memory Internal memory *	16 GB	Number of redundant power supplies supported	2
Internal memory type * Buffered memory type	DDR5-SDRAM Unregistered (unbuffered) 4x DIMM	Number of redundant power supplies installed	2
Memory slots		Power cable length	2 m
ECC		Power cable connector 1	C13 coupler
Memory clock speed 4800 MHz		Power cable connector 2	C14 coupler
	. x 16 GB	Power cable current	10 A
Maximum internal memory *	128 GB	Operational conditions	
Storage Total storage capacity *	480 GB	Storage temperature (T-T) Storage relative humidity (H-H)	-40 - 65 °C 5 - 95%
Number of SSDs installed	1	Operating altitude	0 - 2048 m
SSD capacity	480 GB	Non-operating altitude	0 - 12000 m
SSD interface	SATA III	Carbon footprint	
SSD size	2.5"	Total carbon footprint (kg of CO2e)	1409
RAID support *	✓ PEDCHIZEE	Total carbon emissions, standard deviation (kg of CO2e)	1213
Supported RAID controllers	PERC H755		

Storage		Carbon footprint	
Hot-Plug support	✓	Carbon emissions, manufacturing (kg of CO2e)	296
Optical drive type * Internal drive bays	X 8	Carbon emissions, logistics (kg of CO2e)	155
Graphics		Carbon emissions, energy usage (kg	930
On-board graphics card	x	of CO2e) Carbon emissions, end-of-life (kg of	20
Network		CO2e)	28
LAN controller	Broadcom 5720	Total carbon emissions, w/o use phase (kg of CO2e)	479
Ethernet LAN	✓	PAIA version	1.4.0, 2024
Cabling technology Ethernet interface type	10/100/1000Base-T(X) Gigabit Ethernet	Weight & dimensions	
7.	Olgubic Ethernet	Width	175 mm
Ports & interfaces		Depth	581.1 mm
Ethernet LAN (RJ-45) ports *	2	Height	369.5 mm
USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A	5	Technical details	
ports quantity	2	Supported storage drives form factor (internal)	3.5"
VGA (D-Sub) ports quantity	1	. ,	
Serial ports quantity	1	Other features	
Expansion slots		Data transfer rate	6 Gbit/s
PCI Express x4 slots	2	Bytes per sector	512
Design			
Chassis type *	Tower (4.5U)		

