



TP-Link LiteWave LS1210GP võrgulüliti Mittejuhitav Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product family: LiteWave

Product code: LS1210GP

Product name : LS1210GP



TP-Link LiteWave LS1210GP. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 9. MAC-aadresside tabel: 4000 sisestust, Lülitusvõime: 20 Gbit/s. Võrgustandardid: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE.... Alalisvoolu sisendpinge: 53.5 V. Power over Ethernet tugi



Management features		Power	
Switch type *	Unmanaged	AC input frequency	50 Hz
Quality of Service (QoS) support	✓	DC input voltage	53.5 V
Ports & interfaces		Power consumption (max)	76.96 W
Basic switching RJ-45 Ethernet ports quantity *	9	Power over Ethernet (PoE)	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) *	✓
SFP module slots quantity	1	Power over Ethernet (PoE) ports quantity	8
Network		Power over Ethernet (PoE) power per port	30 W
Networking standards *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Total Power over Ethernet (PoE) budget	61 W
10G support *	✗	Operational conditions	
Cable types supported	Cat3, Cat4, Cat5, Cat5e	Operating temperature (T-T)	0 - 40 °C
Flow control support	✓	Storage temperature (T-T)	-40 - 70 °C
Auto MDI/MDI-X	✓	Operating relative humidity (H-H)	10 - 90%
Auto-negotiation	✓	Storage relative humidity (H-H)	5 - 90%
Data transmission		Heat dissipation	261.66 BTU/h
Switching capacity *	20 Gbit/s	Weight & dimensions	
Forwarding rate	14.88 Mpps	Width	209 mm
MAC address table *	4000 entries	Depth	126 mm
Store-and-forward	✓	Height	26 mm
Jumbo frames	16000	Packaging content	
Design		User guide	✓
Product colour	Black	Packaging data	
LED indicators	✓	Package type	Box
		Certificates	
		Certification	CE, FCC, RoHS

Power

Power source *	DC/PoE
Power supply included *	✓
AC input voltage	220 V



4895252504576

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-JAN-2025. Prints or copies of Information are only valid on the printed Publication date