



TP-Link TL-SG105PP-M2 võrgulüliti Mittejuhitav Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : TP-Link

Product code: TL-SG105PP-M2

Product name : TL-SG105PP-M2



TP-Link TL-SG105PP-M2. Lüliti tüüp: Mittejuhitav. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 5. MAC-aadresside tabel: 4000 sisestust, Lülitusvõime: 25 Gbit/s. Võrgustandardid: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Power over Ethernet tugi



Management features		Performance	
Switch type *	Unmanaged	Fanless	✓
Quality of Service (QoS) support	✓		
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	5	Power source *	DC/PoE
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included *	✓
2.5G Ethernet (copper) ports quantity	5	Number of power supply units	1
Network		AC input voltage	220 V
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	AC input frequency	50 Hz
10G support *	✗	Input current	2.43 A
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Input voltage	53.5 V
Cable types supported	Cat3, Cat4, Cat5, Cat5e	Power consumption (max)	143.37 W
Flow control support	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✓
Auto-negotiation	✓	Power over Ethernet 4PPoE (PoE++) ports quantity	4
MAC address auto-learning supported	✓	Power over Ethernet (PoE) power per port	60 W
MAC address auto-aging supported	✓	Total Power over Ethernet (PoE) budget	123 W
Data transmission		Operational conditions	
Switching capacity *	25 Gbit/s	Operating temperature (T-T)	0 - 40 °C
Forwarding rate	18.6 Mpps	Storage temperature (T-T)	-40 - 70 °C
MAC address table *	4000 entries	Operating relative humidity (H-H)	10 - 90%
Store-and-forward	✓	Storage relative humidity (H-H)	5 - 90%
		Heat dissipation	488.89 BTU/h
		Weight & dimensions	
		Width	209 mm
		Depth	126 mm

Security		Weight & dimensions	
IGMP snooping	✓	Height	26 mm
Design		Packaging content	
Rack mounting *	✗	Cables included	AC
Product colour	Black	User guide	✓
Housing material	Steel	Packaging data	
LED indicators	✓	Package type	Box
		Certificates	
		Certification	CE, FCC, RoHS



4895252501148



4895252501131

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.