



Dahua Technology CS4220-16GT-135 võrgulüliti Juhitav L2 Gigabit Ethernet (10/100/1000) Power over Ethernet tugi Must

Brand : Dahua Technology

Product code: CS4220-16GT-135

Product name : CS4220-16GT-135

Dahua Technology CS4220-16GT-135. Lüliti tüüp: Juhitav, Lüliti kiht: L2. RJ-45 Etherneti ühenduse pesade tüüp: Gigabit Ethernet (10/100/1000), RJ-45 Etherneti ühenduse pesade arv: 18, Installitud SFP moodulite hulk: 2. MAC-aadresside tabel: 8000 sisestust, Lülitusvõime: 40 Gbit/s. Võrgustandardid: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Power over Ethernet tugi. Püstikmontaaž

Management features		Design	
Switch type *	Managed	Product colour	Black
Switch layer	L2	Housing material	Metal
Web-based management	✓	Reset button	✓
Cloud-managed	✓	Power	
Ports & interfaces		Power source *	DC/PoE
Basic switching RJ-45 Ethernet ports quantity *	18	AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input frequency	47/63 Hz
Gigabit Ethernet (copper) ports quantity	18	Input current	3 A
Installed SFP modules quantity *	2	Power consumption (typical)	154 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✓
	10G support *	Power over Ethernet (PoE) ports quantity	16
	Flow control support	Total Power over Ethernet (PoE) budget	135 W
	Ethernet LAN data rates	Operational conditions	
	VLAN support	Operating temperature (T-T)	-10 - 55 °C
Number of VLANs	32	Storage temperature (T-T)	-40 - 70 °C
Data transmission		Operating relative humidity (H-H)	5 - 95%
Switching capacity *	40 Gbit/s	Storage relative humidity (H-H)	5 - 95%
Forwarding rate	29.76 Mpps	Weight & dimensions	
MAC address table *	8000 entries	Width	440 mm
Jumbo frames support	✓	Depth	220 mm
Jumbo frames	15000	Height	44 mm
Packet buffer memory	4 MB	Weight	2.26 kg
Security		Packaging data	
DHCP features	DHCP client	Package width	540 mm
Design		Package depth	342 mm
Rack mounting *	✓	Package height	90 mm
		Package weight	2.91 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-JAN-2025. Prints or copies of Information are only valid on the printed Publication date