



TP-Link Omada SG3428XPP-M2 võrgulüliti Juhitav L2+ 2.5G Ethernet (100/1000/2500) Power over Ethernet tugi 1U Must

Brand : TP-Link

Product family: Omada

Product code: SG3428XPP-M2

Product name : SG3428XPP-M2



TP-Link Omada SG3428XPP-M2. Lüliti tüüp: Juhitav, Lüliti kiht: L2+. RJ-45 Etherneti ühenduse pesade tüüp: 2.5G Ethernet (100/1000/2500), RJ-45 Etherneti ühenduse pesade arv: 24, Konsooli port: RJ-45/Micro-USB. Täisdupleks. MAC-aadresside tabel: 32000 sisestust, Lülitusvõime: 200 Gbit/s. Võrgustandardid: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Power over Ethernet tugi. Püstikmontaaž, Toote kuju: 1U

Management features		Security	
Switch type *	Managed	Authentication	Guest VLAN, MAC-based authentication, Port-based authentication
Switch layer	L2+	Password protection	✓
Quality of Service (QoS) support	✓	Authentication type	AAA, IEEE 802.1x, RADIUS, TACACS+
Web-based management	✓	Queue scheduling algorithms	SP, WRR+SP, Weighted Round Robin (WRR)
Cloud-managed	✓	Multicast features	
ARP inspection	✓	Multicast support	✓
Configuring Location Settings (CLI)	✓	Multicast Listener Discovery (MLD) snooping	MLD v1/v2
System event log	✓	Protocols	
MIB support	RFC1213, RFC2233, RFC1643, RFC1493, RFC2674, RFC2819, RFC2021, RFC2620, RFC2618, RFC2925	Management protocols	SNMP v1/v2c/v3
Ports & interfaces		GARP VLAN Registration Protocol (GVRP)	✓
Basic switching RJ-45 Ethernet ports quantity *	24	IPv4 & IPv6 features	IPv4/IPv6 access-control list (ACL), IPv6 ping, IPv6 portal, IPv6 tracertr
Basic switching RJ-45 Ethernet ports type *	2.5G Ethernet (100/1000/2500)	Design	
2.5G Ethernet (copper) ports quantity	24	Rack mounting *	✓
SFP+ module slots quantity	4	Form factor	1U
Console port	RJ-45/Micro-USB	Product colour	Black
Network		LED indicators	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Redundant fans support	✓
10G support *	✓	Number of fans	3 fan(s)
Port mirroring	✓	Performance	
Full duplex	✓	Memory type	DRAM
Half duplex	✓	Internal memory	256 MB
Flow control support	✓	Flash memory	32 MB
Link aggregation	✓	Power	
Broadcast storm control	✓	Power source *	AC/PoE
Rate limiting	✓	Power supply included *	✓
Spanning tree protocol	✓	Redundant power supply (RPS) support	✓
Head-of-line (HOL) blocking	✓	AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
		Power consumption (max)	629.1 W

Network		Power over Ethernet (PoE)	
Ethernet LAN data rates	10,100,1000,2500,10000 Mbit/s	Power over Ethernet (PoE) *	✓
IPv4 routes	48	Power over Ethernet plus (PoE+) ports quantity	16
IPv6 routes	48	Power over Ethernet 4PPoE (PoE++) ports quantity	8
VLAN support	✓	Total Power over Ethernet (PoE) budget	500 W
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Protocol-based VLAN, Stacked VLAN, Tagged VLAN, Voice VLAN	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 40 °C
Switching capacity *	200 Gbit/s	Storage temperature (T-T)	-40 - 70 °C
Forwarding rate	148.8 Mpps	Operating relative humidity (H-H)	10 - 90%
MAC address table *	32000 entries	Storage relative humidity (H-H)	5 - 90%
Store-and-forward	✓	Heat dissipation	2153.45 BTU/h
Number of queues	8	Weight & dimensions	
Static route	✓	Width	440 mm
Number of static routes	48	Depth	330 mm
Number of IP interfaces	32	Height	44 mm
Jumbo frames support	✓	Packaging content	
Jumbo frames	9000	Cables included	AC
Packet buffer memory	16 MB	Quick start guide	✓
Security		Rack mount kit	✓
DHCP features	DHCP client, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 snooping	Sustainability	
Access Control List (ACL)	✓	Sustainability compliance	✓
IGMP snooping	✓	Certificates	
Security algorithms	HTTPS, SSH, SSH-2, SSL/TLS	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
Static port security	✓		
SSH/SSL support	✓		
Loop protection	✓		
BPDU filtering/protection	✓		
IP-MAC-Port binding	✓		



4897098689738



0840030709739



840030709739

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.