

TP-Link Omada EAP772 traadita kohtvõrgu pääsupunkt 9300 Mbit/s Valge

Brand : TP-Link

Features

Product family: Omada

Product code: EAP772

Product name : EAP772

TP-Link Omada EAP772. 2,4 GHz, 5 GHz, 6 GHz, Andmete edastamise maksimaalne määr: 9300 Mbit/s. Turvaalgoritmid: SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal,.... Ethernet LAN-i andmeedastuskiirused: 2500 Mbit/s. Toote värv: Valge






		,		
2.4 GHz *	1	Remote Authentication Dial-In User Service (RADIUS)	1	
5 GHz *	 Image: A set of the set of the	Access Control List (ACL)	1	
6 GHz *	✓	× ,	-	
Maximum data transfer rate *	9300 Mbit/s	Management features		
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Web-based management	1	
Maximum data transfer rate (5 GHz)	2880 Mbit/s	Ports & interfaces		
Maximum data transfer rate (6 GHz)	5760 Mbit/s	Ethernet LAN (RJ-45) ports *	1	
Ethernet LAN data rates	2500 Mbit/s	Design		
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n	Placement * Product colour * LED indicators	Ceiling, Wall White	
Number of users	380 user(s)			
Bluetooth	1	Antenna		
Bluetooth version	5.2	Antenna type *	Internal	
МІМО	1	Certificates		
MIMO type	Multi User MIMO	Certification	CE, FCC, RoHS, IC	
VLAN support	✓	Weight & dimensions		
Airtime Fairness (ATF)	 Image: A set of the set of the	Width	220 mm	
Quality of Service (QoS) support	1	Depth	220 mm	
BeamForming	 Image: A second s	Height	32.5 mm	
Security		Packaging content		
Security algorithms *	SNMP, SNMPv2, SNMPv3, WPA- Enterprise, WPA-Personal, WPA2- Enterprise, WPA2-Personal, WPA3- Enterprise, WPA3-Personal	Quantity per pack AC adapter included Mounting kit	1 pc(s) ★ ✓	
MAC address filtering	1	Operational conditions		
		Operating relative humidity (H-H)	10 - 90%	

Security


Security		Operational conditions	
Service Set Identifier (SSID) features Number of SSID supported	Multiple SSIDs 24	Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 5 - 90%











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.