

## TP-Link Omada EAP783 traadita kohtvõrgu pääsupunkt 19000 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link Product family: Omada Product code: EAP783

**Product name:** EAP783


TP-Link Omada EAP783. 2,4 GHz, 5 GHz, 6 GHz, Andmete edastamise maksimaalne määr: 19000 Mbit/s. Turvaalgoritmid: WPA, WPA2, WPA3. Ethernet LAN-i andmeedastuskiirused: 10000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge





Features		Ports & interfaces	
2.4 GHz *	✓	Ethernet LAN (RJ-45) ports *	2
5 GHz *	✓	DC-in jack	✓
6 GHz *	✓	Power	
Maximum data transfer rate *	19000 Mbit/s	Power over Ethernet (PoE) *	/
Maximum data transfer rate (2.4 GHz)	1376 Mbit/s	DC voltage range	12 V
Maximum data transfer rate (5 GHz)	5760 Mbit/s	Design	
Maximum data transfer rate (6 GHz)	11520 Mbit/s	Placement *	Ceiling, Wall
Ethernet LAN data rates	10000 Mbit/s	Product colour *	White
Frequency band	2.4 - 6 GHz	Reset button	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n	LED indicators	✓
		Antenna	
Number of users	760 user(s)	Antenna type *	Internal
Automatic channel selection	✓	Weight & dimensions	
Automatic channel scanning	✓	Width	280 mm
MIMO	✓	Depth	280 mm
MIMO type	Multi User MIMO	Height	46.5 mm
MIMO type VLAN support	Multi User MIMO ✓	Height  Packaging data	46.5 mm
• •			46.5 mm Box
VLAN support	<b>✓</b>	Packaging data	
VLAN support Rate limiting	<i>y</i>	Packaging data Package type	
VLAN support Rate limiting Flow control support	<i>y</i>	Packaging data Package type Packaging content	Вох
VLAN support Rate limiting Flow control support Band steering	<i>y</i>	Packaging data Package type Packaging content Quantity per pack	Box 1 pc(s)
VLAN support Rate limiting Flow control support Band steering Airtime Fairness (ATF)	* * * * * * * * * * * * * * * * * * *	Packaging data Package type Packaging content Quantity per pack Mounting kit	Box 1 pc(s) ✓
VLAN support Rate limiting Flow control support Band steering Airtime Fairness (ATF) Quality of Service (QoS) support		Packaging data Package type Packaging content Quantity per pack Mounting kit Quick start guide	Box 1 pc(s) ✓

Security		Operational conditions
Access Control List (ACL)	✓	Storage temperature (T-T) -40 - 70 °C
		Storage relative humidity (H-H) 5 - 90%





840030710070

0840030710070



4895252503517

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.