## ProDVX APPC-10SLBe Panel PC (R24-7701) Rockchip RK3399 25,6 cm (10.1") 1280 x 800 pikslit Puutetundlik ekraan All-in-One tablet PC 4 GB DDR4-SDRAM 16 GB Välk Android 11 Wi-Fi 4 (802.11n) Must



**Brand : ProDVX** Product code: 5010825

Product name: APPC-10SLBe Panel PC (R24-7701)

ProDVX APPC-10SLBe Panel PC (R24-7701). Toote tüüp: All-in-One tablet PC. Ekraani diagonaal: 25,6 cm (10.1"), Ekraani resolutsioon: 1280 x 800 pikslit, Puutetundlik ekraan, Paneeli tüüp: IPS. Protsessori perekond: Rockchip. Sisemälu: 4 GB, Sisemälu tüüp: DDR4-SDRAM. Salvestusmaht kokku: 16 GB, Salvestusseade: Välk. Pardagraafika adapteri mudel: ARM Mali-T860 MP4. Installitud operatsioonisüsteem: Android 11. Toote värv: Must



Display		Network	
Display diagonal * Display resolution * Touchscreen * Touch technology Native aspect ratio Display brightness Panel type Contrast ratio (typical) Viewing angle, horizontal	25.6 cm (10.1") 1280 x 800 pixels  ✓  Multi-touch 16:10 500 cd/m² IPS 800:1 160°	Bluetooth version	4.2
		Ports & interfaces	
		Ethernet LAN (RJ-45) ports USB 2.0 ports quantity * HDMI ports quantity * Audio output DC-in jack Micro-USB ports quantity	1 1 1 •
Viewing angle, vertical	160°	Design	
Multi-touch Anti-glare screen	<b>✓</b>	Product colour * Wall mountable	Black ✓
Processor		Housing material	Plastic
	Rockchip Rockchip	VESA mounting Panel mounting interface	✓ 75 x 75 mm
Processor model *	RK3399	Performance	
Processor cores	6	Product type *	All-in-One tablet PC
Memory		Software	
Internal memory * Internal memory type	4 GB DDR4-SDRAM	Operating system installed *  Power	Android 11
Storage		AC adapter output voltage	12 V
Total storage capacity *	16 GB	Weight & dimensions	
Storage media * Card reader integrated Compatible memory cards Graphics		Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	255.3 mm 26.7 mm 181 mm 650 g
Discrete graphics card *	×	Operational conditions	
Discrete graphics card model * On-board graphics card * On-board graphics card model *	Not available ✓  ARM Mali-T860 MP4	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -10 - 55 °C 10 - 90%
Audio		Storage relative humidity (H-H)	10 - 90%
Built-in speaker(s) *	✓		

Audio		Certificates	
Number of speakers	2	Certification	FCC, CE, RoHS
RMS rated power	4 W	Packaging content	
Built-in microphone	<b>✓</b>	Cables included	No
Camera		Logistics data	
Built-in camera *	X	Harmonized System (HS) code	84713000
Network		Other features	
Wi-Fi *	✓	Mean time between failures (MTBF)	50000 h
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	Backlight type	Edge LED
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Backlight	✓
Ethernet LAN *	<b>✓</b>	Near Field Communication (NFC)	
Ethernet LAN data rates	10,100,1000 Mbit/s		
Bluetooth *	<b>✓</b>		

