



TP-Link Archer VR400 juhtmevaba ruuter Gigabit Ethernet Kaks sagedusala (2,4 GHz / 5 GHz) Must

Brand : TP-Link

Product code: ARCHER VR400 V2

Product name : Archer VR400

TP-Link Archer VR400. WAN-ühenduse tüüp: RJ-45. Wi-Fi laineala: Kaks sagedusala (2,4 GHz / 5 GHz), Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN edastuskiirus (max): 867 Mbit/s. Ethernet LAN-liidese tüüp: Gigabit Ethernet, Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s, Kaabeldustehnoloogia: 10/100/1000Base-T(X). Turvaalgoritmid: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Haldusprotokollid: SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools, Toetatud võrguprotokollid: IPv4, IPv6



WAN connection		Protocols	
Ethernet WAN *	✓	DHCP client	✓
DSL WAN *	✓	DHCP server	✓
SIM card slot *	✗	Universal Plug and Play (UPnP)	✓
3G/4G USB modem compatibility *	✓	Management protocols	SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools
WAN connection type	RJ-45	Supported network protocols	IPv4, IPv6
Wireless LAN features		Design	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Product colour	Black
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac)	Wall mountable	✓
WLAN data transfer rate (max) *	867 Mbit/s	Indication light	✓
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n)	LED indicators	LAN, Power, WLAN
WLAN data transfer rate (first band)	300 Mbit/s	On/off switch	✓
WLAN data transfer rate (second band)	867 Mbit/s	Product type *	Tabletop router
Network		Certificates	
Ethernet LAN *	✓	Certification	CE, RoHS
Ethernet LAN interface type *	Gigabit Ethernet	Packaging content	
Ethernet LAN data rates	10,100,1000 Mbit/s	Cables included	LAN (RJ-45)
Cabling technology	10/100/1000Base-T(X)	AC adapter included	✓
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Manual	✓
Port forwarding	✓	Quick start guide	✓
Dynamic DNS (DDNS)	✓	Antenna	
Static route	✓	Antenna design *	External
VPN tunnels quantity	10	Antennas quantity	3
VPN Passthrough	✓	Detachable antenna(s)	✓
VPN support	PTP, L2TP, IPSec Passthrough		

DSL features		Power	
ADSL	✓	Power source type *	AC
ADSL2	✓	Output voltage	12 V
ADSL2+	✓	Output current	1.5 A
VDSL2	✓	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
		Storage temperature (T-T)	-40 - 70 °C
		Operating relative humidity (H-H)	10 - 90%
		Storage relative humidity (H-H)	5 - 90%
		System requirements	
Ethernet LAN (RJ-45) ports *	5	Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
USB port *	✓		
USB 2.0 ports quantity	1		
Memory card slot(s)	✗		
DC-in jack	✓		
Management features			
Quality of Service (QoS) support	✓		
Reset button	✓		
WPS push button	✓		
Security			
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK		
Firewall	✓		
Guest access	✓		
Access Control List (ACL)	✓		
Filtering	✓		
MAC address filtering	✓		
DMZ support	✓		
		Windows operating systems supported	
		Linux operating systems supported	✓
		Mac operating systems supported	✓
Weight & dimensions			
		Width	215.6 mm
		Depth	124.6 mm
		Height	31.6 mm
Packaging data			
		Package width	350 mm
		Package depth	240 mm
		Package height	82 mm
		Package weight	850 g
		Package type	Box



6935364096854



0845973096854



845973096854



6935364096861

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-JAN-2025. Prints or copies of Information are only valid on the printed Publication date