



## QNAP TS-433eU NAS Püstik (1U) Cortex-A Cortex-A55 4 GB 0 TB QNAP Turbo System Must



**Brand :** QNAP

**Product code:** TS-433EU

**Product name :** TS-433eU



QNAP TS-433eU. Tüüp: NAS. Keretüüp: Püstik (1U). Seadme klass: Väike ja keskmise suurusega ettevõtte.  
Protsessori perekond: Cortex-A, Protsessori mudel: Cortex-A55, Protsessori sagedus: 2 GHz. Sisemälu: 4 GB. Installeeritud mälu maht kokku: 0 TB. Installitud operatsioonisüsteem: QNAP Turbo System

Storage		Performance	
Storage drive interface *	Serial ATA	Type *	NAS
Storage drive size	2.5/3.5"	Device class *	Small & Medium Business
RAID support *	✗	Buzzer	✓
Hot-swap drive bays	✓	Reset button	✓
Storage drives installed *	✗	On/off switch	✓
Total installed storage capacity *	0 TB	Built-in FTP server	✓
Number of storage drives supported *	4	Browser supported	Microsoft Internet Explorer 10+, Mozilla Firefox 8+, Apple Safari 4+, Google Chrome
Installed storage drive type *	✗	Hot spare	✓
Supported storage drive types *	HDD & SSD	Share folder	CIFS/SMB
Processor		Software	
Processor manufacturer *	ARM	Operating system installed *	QNAP Turbo System
Processor family *	Cortex-A	Operating system version	4.1
Processor model *	Cortex-A55	Windows operating systems supported	✓
Processor frequency *	2 GHz	Linux operating systems supported	✓
Processor cores	4	Mac operating systems supported	✓
Processor architecture	ARM Cortex-A55		
Memory		Power	
Internal memory *	4 GB	Power supply location	Built-in
Network		Power supply unit (PSU) capacity	60 W
Ethernet LAN *	✓	Number of power supply units	1
Ethernet LAN data rates	1000,2500 Mbit/s	Power consumption (typical)	23.74 W
Wake-on-LAN ready	✓	Power consumption (sleep)	9.32 W
Ports & interfaces		AC input voltage	100-240 V
USB port *	✓	Fan voltage	12 V
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2	Weight & dimensions	
Ethernet LAN (RJ-45) ports *	2	Width *	430 mm
Design		Depth *	292.3 mm
Chassis type *	Rack (1U)	Height *	292.3 mm
Cooling type *	Active	Weight	4.01 kg
Product colour	Black	Package weight	5.9 kg
Number of fans	3 fan(s)	Operational conditions	
Fan diameter	4 cm	Operating temperature (T-T)	0 - 40 °C
LED indicators	HDD, LAN, Status, USB	Operating relative humidity (H-H)	5 - 95%
Cable lock slot	✓	Storage temperature (T-T)	-20 - 70 °C
Cable lock slot type	Kensington		



4711103085943

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-JAN-2025. Prints or copies of Information are only valid on the printed Publication date