ïiyama

iiyama ProLite XU2792UHSU-B6 PC lamekuvar 68,6 cm (27") 3840 x 2160 pikslit 4K Ultra HD LED Must

Brand : iiyama

Product name : XU2792UHSU-B6

Product family: ProLite

Product code: XU2792UHSU-B6

iiyama ProLite XU2792UHSU-B6. Ekraani diagonaal: 68,6 cm (27"), Ekraani resolutsioon: 3840 x 2160 pikslit, HD tüüp: 4K Ultra HD, Ekraani tehnoloogia: LED, Reaktsiooniaeg: 4 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud kõlar(id). Sisseehitatud USB-jaotur, USB-jaoturi versioon: 3.2 Gen 1 (3.1 Gen 1). VESA paigaldamine. Toote värv: Must

Display

Display diagonal *	68.6 cm (27")
Display resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Native aspect ratio *	16:9
Display technology *	LED
Panel type *	IPS
Touchscreen *	✘
Display brightness (typical)	350 cd/m²
Response time *	4 ms
Aspect ratio	16:10
Contrast ratio (typical) *	1300:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
Pixel pitch	0.155 x 0.155 mm
Horizontal scan range	30 - 140 kHz
Viewable size, horizontal	59.7 cm
Viewable size, vertical	33.6 cm
Display diagonal (metric)	68.5 cm

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Flicker-free technology	✔

Multimedia

Number of speakers	2
RMS rated power	4 W
Built-in speaker(s) *	✔
Built-in camera *	✘

Ports & interfaces

DisplayPort version	1.2
Headphone out *	✔
Headphone connectivity	3.5 mm
HDCP	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable management	✔
Height adjustment *	✘
Tilt adjustment	✔
Tilt angle range	4 - 20°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Czech, German, English, Spanish, French, Italian, Japanese, Polish, Russian

Power

Energy efficiency class (SDR) *	F
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	26 kWh
Energy consumption (HDR) per 1000 hours *	0 kWh
Power consumption (typical) *	34 W
Power consumption (standby) *	0.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	1955520

Weight & dimensions

Width (with stand)	614.5 mm

Design

Market positioning *	Business
Product colour *	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-C
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	15 W
HDMI *	✔
HDMI ports quantity	1
HDMI version	2.0
DisplayPorts quantity	1

Weight & dimensions

Depth (with stand)	190 mm
Height (with stand)	439.5 mm
Weight (with stand)	4.7 kg

Packaging data

Package width	688 mm
Package depth	124 mm
Package height	473 mm
Package weight	7.1 kg

Packaging content

Cables included	HDMI, Power, USB
Quick start guide	✔

Other features

Certification	TCO Certified, CE, TÜV-GS, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA

4948570123797