*iiyama*

# iiyama ProLite XUB2497HSN-W2 PC lamekuvar 60,5 cm (23.8") 1920 x 1080 pikslit Full HD LED Valge

**Brand :** iiyama

**Product family:** ProLite

**Product code:** XUB2497HSN-W2

**Product name :** XUB2497HSN-W2

iiyama ProLite XUB2497HSN-W2. Ekraani diagonaal: 60,5 cm (23.8"), Ekraani resolutsioon: 1920 x 1080 pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LED, Ekraani pind: Matt, Reaktsiooniaeg: 1 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud kõlar(id). Sisseehitatud USB-jaotur, USB-jaoturi versioon: 3.2 Gen 1 (3.1 Gen 1). VESA paigaldamine, Kõrguse reguleerimine. Toote värv: Valge

## Display

| | |
|---|---|
| Display diagonal * | 60.5 cm (23.8") |
| Display resolution * | 1920 x 1080 pixels |
| HD type * | Full HD |
| Native aspect ratio * | 16:9 |
| Display technology * | LED |
| Panel type * | IPS |
| Touchscreen * | ✘ |
| Display brightness (typical) | 300 cd/m² |
| Response time * | 1 ms |
| Response time (MPRT) | 1 ms |
| Display surface | Matt |
| Screen shape * | Flat |
| Contrast ratio (typical) * | 1300:1 |
| Contrast ratio (dynamic) | 80000000:1 |
| Maximum refresh rate * | 100 Hz |
| Viewing angle, horizontal | 178° |
| Viewing angle, vertical | 178° |
| Display number of colours * | 16.7 million colours |
| Pixel pitch | 0.275 x 0.275 mm |
| Horizontal scan range | 30 - 110 kHz |
| Viewable size, horizontal | 52.7 cm |
| Viewable size, vertical | 29.6 cm |
| DDC/CI | ✔ |
| Colour gamut standard | NTSC, sRGB |
| sRGB coverage (typical) | 99% |
| NTSC coverage (typical) | 72% |

## Ergonomics

| | |
|---|---|
| VESA mounting * | ✔ |
| Panel mounting interface | 100 x 100 mm |
| Wall mountable | ✔ |
| Cable management | ✔ |
| Cable lock slot * | ✔ |
| Cable lock slot type | Kensington |
| Height adjustment * | ✔ |
| Adjustable height (max) | 15 cm |
| Pivot | ✔ |
| Pivot angle | 0 - 90° |
| Swivelling | ✔ |
| Swivel angle range | 45 - 90° |
| Tilt adjustment | ✔ |
| Tilt angle range | 5 - 23° |
| On Screen Display (OSD) | ✔ |
| On Screen Display (OSD) languages | Czech, German, Dutch, English, Spanish, French, Italian, Japanese, Polish, Russian |

## Power

| | |
|---|---|
| Energy efficiency class (SDR) * | E |
| Energy efficiency class (HDR) * | Not available |
| Energy consumption (SDR) per 1000 hours * | 18 kWh |
| Power consumption (typical) * | 20 W |
| Power consumption (standby) * | 0.5 W |
| Power consumption (off) | 0.3 W |
| AC input voltage | 100 - 240 V |

## Performance

| | |
|---|---|
| VESA Adaptive Sync support | ✔ |
| Flicker-free technology | ✔ |
| Low Blue Light technology | ✔ |

## Multimedia

| | |
|---|---|
| Number of speakers | 2 |
| RMS rated power | 4 W |
| Built-in speaker(s) * | ✔ |

## Design

| | |
|---|---|
| Market positioning * | Business |
| Product colour * | White |

## Ports & interfaces

| | |
|---|---|
| Built-in USB hub * | ✔ |
| USB hub version | 3.2 Gen 1 (3.1 Gen 1) |
| USB Power Delivery (USB PD) | ✔ |
| USB Power Delivery up to | 65 W |
| HDMI * | ✔ |
| HDMI ports quantity | 1 |
| HDMI version | 1.4 |
| DisplayPorts quantity | 1 |
| DisplayPort out version | 1.2 |
| Headphone out * | ✔ |
| HDCP | ✔ |

## Network

| | |
|---|---|
| Ethernet LAN | ✔ |

## Power

| | |
|---|---|
| AC input frequency | 50/60 Hz |
| Power supply type | Internal |
| Energy efficiency scale | A to G |

## Weight & dimensions

| | |
|---|---|
| Width (with stand) | 538.5 mm |
| Depth (with stand) | 209.5 mm |
| Height (with stand) | 500 mm |
| Weight (with stand) | 5.3 kg |
| Width (without stand) | 538.5 mm |
| Depth (without stand) | 209.5 mm |
| Height (without stand) | 350 mm |

## Packaging data

| | |
|---|---|
| Package width | 685 mm |
| Package depth | 126 mm |
| Package height | 405 mm |
| Package weight | 7.4 kg |
| Package type | Box |

## Packaging content

| | |
|---|---|
| Cables included | AC, HDMI, USB Type-C |
| Quick start guide | ✔ |

## Other features

| | |
|---|---|
| Warranty period | 5 year(s) |

4948570124954