

# Vertiv Liebert GXE3-1000IRT2UXL puhvertoiteallikas (UPS) Online UPS 1 kVA 900 W 8 vahelduvvoolu kontakt

**Brand :** Vertiv

**Product family:** Liebert

**Product code:**  
GXE3-1000IRT2UXL

**Product name :**  
GXE3-1000IRT2UXL

Vertiv Liebert GXE3-1000IRT2UXL. Puhvertoiteallika topoloogia: Online UPS, Väljundvõimsuse potentsiaal: 1 kVA, Väljundvõimsus: 900 W. AC-väljundi tüüp: C13 pistikut, AC-väljundite arv: 8 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Tüübipärane varundamisaeg täiskoormusega: 3,1 min, Tüübipärane varundamisaeg poole koormusega: 9 min. Toote kuju: Rackmount/Tower, Toote värv: Hall, Püstiku mahutavus: 2U. Vastavussertifikaadid: CB, CE, RCM, REACH, RoHS, UKCA, WEEE



Features		Battery	
UPS topology *	Double-conversion (Online)	Battery life (max)	5 year(s)
Output power capacity *	1 kVA	Battery recharge time	4 h
Output power *	900 W	<b>Design</b>	
Waveform *	Pure sine	Form factor *	Rackmount/Tower
Input operation voltage (min) *	110 V	Rack capacity	2U
Input operation voltage (max) *	290 V	Product colour *	Grey
Input frequency *	40 - 70 Hz	Display type	LCD
Output operation voltage (min)	220 V	<b>Operational conditions</b>	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	600 J	Storage temperature (T-T)	-20 - 50 °C
Efficiency (On-line mode)	89%	Operating relative humidity (H-H)	5 - 90%
Efficiency (ECO mode)	95%	Operating altitude	0 - 2000 m
EMI/RFI noise filtering	✓	<b>Certificates</b>	
Noise level	53 dB	Compliance certificates	CB, CE, RCM, REACH, RoHS, UKCA, WEEE
<b>Ports &amp; interfaces</b>		<b>Packaging content</b>	
AC outlet types	C13 coupler	Cables included	Input power cable, Output power cable, USB cable
AC outlets quantity	8 AC outlet(s)	Quick installation guide	✓
USB port	✓	<b>Sustainability</b>	
Emergency Power Off (EPO) connector	✓	Sustainability compliance	✓
<b>Battery</b>		<b>Weight &amp; dimensions</b>	
Battery technology	Sealed Lead Acid (VRLA)	Width	438 mm
Number of batteries supported	2	Depth	430 mm
Typical backup time at full load	3.1 min	Height	86 mm
Typical backup time at half load	9 min	Weight	16 kg
		<b>Packaging data</b>	
		Package width	235 mm
		Package depth	600 mm
		Package height	560 mm
		Package weight	17.6 kg

**Logistics data**

Country of origin

China



0767041034394



767041034394

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.