Vertiv Liebert GXE3-3000IRT2UXL puhvertoiteallikas (UPS) Online UPS 3 kVA 2700 W 9 vahelduvvoolu kontakt

Brand : Vertiv

Product family: Liebert

Product code: GXE3-3000IRT2UXL

Product name : GXE3-3000IRT2UXL

Vertiv Liebert GXE3-3000IRT2UXL. Puhvertoiteallika topoloogia: Online UPS, Väljundvõimsuse potentsiaal: 3 kVA, Väljundvõimsus: 2700 W. AC-väljundi tüüp: C13 pistikut, C19 pistikut, AC-väljundite arv: 9 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Tüübipärane varundamisaeg täiskoormusega: 3,3 min, Tüübipärane varundamisaeg poole koormusega: 9,5 min. Toote kuju: Rackmount/Tower, Toote värv: Hall, Püstiku mahutavus: 2U. Vastavussertifikaadid: CB, CE, RCM, REACH, RoHS, UKCA, WEEE





Features		Battery	
Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min)	Double-conversion (Online) 3 kVA 2700 W Pure sine 110 V 290 V 40 - 70 Hz 220 V 240 V	Typical backup time at half load Battery life (max) Battery recharge time	9.5 min 5 year(s) 4 h
		Design Form factor * Rack capacity Product colour * Display type	Rackmount/Tower 2U Grey LCD
Surge energy rating	600 J	Operational conditions	
Efficiency (On-line mode) Efficiency (ECO mode) EMI/RFI noise filtering Noise level	91% 96% ✓ 53 dB	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude	0 - 40 °C -20 - 50 °C 5 - 90% 0 - 2000 m
Ports & interfaces		Certificates	
AC outlet types AC outlets quantity	C13 coupler, C19 coupler 9 AC outlet(s)	Compliance certificates	CB, CE, RCM, REACH, RoHS, UKCA, WEEE
USB port	<	Packaging content	
Emergency Power Off (EPO) connector	✓	Cables included	Input power cable, Output power cable, USB cable
Battery		Quick installation guide	1
Battery technology	Sealed Lead Acid (VRLA)	Sustainability	
Number of batteries supported Typical backup time at full load	6 3.3 min	Sustainability compliance	1
		Weight & dimensions	
		Width Depth Height	438 mm 630 mm 86 mm

Weight & dimensions		
Weight	31.5 kg	
Packaging data		
Package width	790 mm	
Package depth	600 mm	
Package height	235 mm	
Package weight	34.2 kg	





767041034424

0767041034424

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.