tp-link

TP-Link Tapo C510W Ülepea IP süsteemiga turvakaamera
Hoonesisene & hooneväline 2304 x 1296 pikslit Lagi

Brand : TP-Link　　　　**Product family:** Tapo　　　　**Product code:** TAPO C510W

Product name : Tapo C510W

TP-Link Tapo C510W. Tüüp: IP süsteemiga turvakaamera, Toetatud paigutus: Hoonesisene & hooneväline, Ühenduvustehnoloogia: Juhtmevaba. Kinnituse tüüp: Lagi, Toote värv: Valge, Must, Toote kuju: Ülepea. Objektiivi vaatenurk, horisontaalne: 360°, Objektiivi vaatenurk, vertikaalne: 130°, Kaldenurk: 0 - 130°. Anduri tüüp: CMOS, Optilise sensori suurus: 25,4 / 2,8 mm (1 / 2.8"). Fikseeritud fookuskaugus: 3,9 mm

Performance

Type *	IP security camera
Placement supported *	Indoor & outdoor
Connectivity technology *	Wireless
Certification	CE, FCC, RoHS, RCM

Design

Form factor *	Dome
Mounting type *	Ceiling
Product colour *	White, Black
LED indicators	✔
International Protection (IP) code	IP65

Camera

Lens viewing angle, horizontal	360°
Lens viewing angle, vertical	130°
Tilt angle range	0 - 130°
Pan range	0 - 360°

Image sensor

Number of sensors	1
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")
Sensor type *	CMOS

Lens system

Number of lenses *	1
Maximum aperture number	2
Fixed focal length	3.9 mm

Night vision

Night vision *	✔
Night vision distance	30 m
LED type	IR

Video

Maximum resolution *	2304 x 1296 pixels
Total megapixels *	3 MP
Video formats supported	H.264
Supported graphics resolutions	2304 x 1296
Frame rate	15 fps

Audio

Built-in speaker(s)	✔
Built-in microphone	✔

Network

Ethernet LAN *	✘
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Supported network protocols	TCP/IP, ICMP, DNS, HTTPS, TCP, UDP
Wi-Fi *	✔
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Bluetooth *	✘
Channel bandwidth	2400 MHz

Storage

Built-in HDD *	✘
Card reader integrated	✔
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	512 GB

Ports & interfaces

DC-in jack	✔

Security

Security algorithms	128-bit AES, WPA-PSK, WPA2-PSK

Management features

Reset button	✔

Power

Power source type *	AC
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
DC output voltage	12
DC output current	1 A

Operational conditions

Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	123.8 mm
Depth	123 mm
Height	90 mm

Packaging content	
Number of cameras *	1
Mounting kit	✔
Mounting brackets included	✔
Screws included	✔
Manual	✔

4895252501582

4895252501575