## **NOC**

## AOC E3 24E3QAF LED display 60,5 cm (23.8") 1920 x 1080 pikslit Full HD LCD Must

Brand : AOC Product family: E3 Product code: 24E3QAF

**Product name:** 24E3QAF

AOC E3 24E3QAF. Ekraani diagonaal: 60,5 cm (23.8"), Ekraani resolutsioon: 1920 x 1080 pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LCD, Reaktsiooniaeg: 4 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178°, Vaatenurk, vertikaalne: 178°. Sisseehitatud kõlar(id). VESA paigaldamine, Kõrguse reguleerimine. Toote värv: Must





Display		Ergonomics	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * LED backlight Backlight type Touchscreen * Response time * Anti-glare screen Screen shape * Contrast ratio (typical) * Contrast ratio (dynamic) Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Pixel density	60.5 cm (23.8")  1920 x 1080 pixels  Full HD  16:9  LCD  IPS  W-LED  X  4 ms  Flat  1000:1  20000000:1  75 Hz  178°  178°  0.2745 x 0.2745 mm	Cable lock slot * Cable lock slot type Height adjustment * Adjustable height (max) Pivot Pivot angle Swivelling Swivel angle range Tilt adjustment Tilt angle range On Screen Display (OSD)  On Screen Display (DSD)  Number of OSD languages Plug and Play LED indicators	Kensington  15 cm  -90 - 90°  0 - 180°  Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish  16
Horizontal scan range	93 ppi 30 - 85 kHz	Power	
Vertical scan range Viewable size, horizontal Viewable size, vertical Digital horizontal frequency Digital vertical frequency Display diagonal (metric) High Dynamic Range (HDR) supported DDC/CI	48 - 75 Hz 52.7 cm 29.6 cm 30 - 85 kHz 48 - 75 Hz 60.47 cm	Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type	18 W 0.5 W 35 W 0.3 W 100 - 240 V 50/60 Hz 1.5 A Internal
000,01	•		

Diamlan		On a making all and the control of	
Display	211	Operational conditions	0. 40.00
Surface hardness  Performance	3H	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -25 - 55 °C
Fast charging	×	Operating relative humidity (H-H)	10 - 85%
VESA Adaptive Sync support	···	Storage relative humidity (H-H) Operating altitude	5 - 93% 0 - 5000 m
Flicker-free technology	<b>✓</b>	Non-operating altitude	0 - 3000 m 0 - 12192 m
Low Blue Light technology	<b>✓</b>	Weight & dimensions	0 12132 III
Game mode	<b>✓</b>	Width (with stand)	540 mm
Multimedia		Depth (with stand)	200.1 mm
Number of speakers	2	Height (with stand)	503.6 mm
Built-in speaker(s) *	<b>✓</b>	Weight (with stand)	4.45 kg
Built-in microphone	×	Width (without stand)	540 mm
Built-in camera *	×	Depth (without stand)	50.7 mm
Docien		Height (without stand) Weight (without stand)	362.3 mm 2.63 kg
Design  Market positioning *	Office		2.03 kg
Product colour *	Black	Packaging data	(12
Frameless design	✓	Package width Package depth	613 mm 162 mm
Front bezel colour	Black	Package height	519 mm
Detachable stand	1	Package weight	7.14 kg
Feet colour	Black	Packaging content	
Ports & interfaces		Stand included	1
Built-in USB hub *	×	Cables included	AC, DisplayPort, HDMI
VGA (D-Sub) ports quantity	1	Quick start guide	✓
HDMI *	✓	Sustainability	
HDMI ports quantity	1		
HDMI version	1.4	Sustainability compliance	FREAT Ciliana TCO
DisplayPorts quantity	1	Sustainability certificates	EPEAT Silver, TCO
DisplayPort version	1.2	Other features	
Audio input	✓	FPS counter	<b>✓</b>
Headphone out *	•	Dial point	<b>✓</b>
Headphone outputs	1	Shadow control	<b>✓</b>
Headphone connectivity	3.5 mm	Compatibility	VESA-P2
HDCP HDCP version	1 4	Exterior finish type	Textured
AC (power) in	1.4	Recyclable packaging material	100%
		Warranty period	3 year(s) CB, CE, EAC, Federal
Mobile High-Definition Link (MHL) <b>Ergonomics</b>	×	Compliance certificates	Communications Commission (FCC), RoHS, cTUVus, WEEE
VESA mounting *	✓	Light effects	×
Panel mounting interface	100 x 100 mm	Certification	ISO 9241-307
Cable management	•	Recycling data	
		Post-consumer recycled plastic	85%



4038986141253

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.