



Lindy 73441 mobiilseadme laadija Universaalne Valge

Vahelduvvool Kiirlaadimine Hoonesisene

Brand : Lindy

Product code: 73441

Product name : 73441

Lindy 73441. Laadija tüüp: Hoonesisene, Toiteallika tüüp: Vahelduvvool, Laadija ühilduvus: Universaalne. Sisendpinge: 100 - 240 V, Väljundpinge (max): 12 V, AC-adaptori väljundvool: 3 A. USB 2.0 portide arv: 2, USB C-tüüpi portide arv: 2, Kiirlaadimine, Toite kaitsefunktsioonid: Ülevool, Ülepinge, Ülekütmine, Lühis. Kaabli pikkus: 1,5 m, Toote värv: Valge



Performance		Power	
Charger compatibility *	Universal	AC adapter output current	3 A
Power source type *	AC	Port 1 output power	45 W
USB 2.0 ports quantity	2	Port 2 output power	45 W
USB Type-C ports quantity	2	Port 3 output power	60 W
Fast charging	✓	Port 4 output power	65 W
Fast charging technology	Adaptive Fast Charging, Power Delivery	Output current (5V)	3 A
Sockets quantity	2	Output current (9V)	2 A
Socket type	Type C (Europlug)	Output current (12V)	1.5 A
Charger type *	Indoor	Power consumption (no load)	0.1 W
Number of simultaneously connected devices (max) *	4	Efficiency at low load (10%)	✓
Programmable power supply (PPS)	✓	Power plug type	Type C
Number of outputs	4 outputs	Weight & dimensions	
USB Power Delivery (USB PD)	✓	Width	90 mm
Operating principle	Contact	Depth	40 mm
USB Power Delivery revision	3.0	Height	40 mm
Power protection features	Over current, Over voltage, Overheating, Short circuit	Weight	210 g
Design		Packaging data	
Product colour *	White	Package weight	364 g
Cable length	1.5 m	Package type	Carton
Housing material	Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)	Operational conditions	
Connector material	Copper	Operating temperature (T-T)	0 - 40 °C
Gallium nitride (GaN) transistors	✓	Storage temperature (T-T)	-20 - 70 °C
Power		Operating relative humidity (H-H)	10 - 90%
Input voltage	100 - 240 V	Storage relative humidity (H-H)	5 - 95%
		Packaging content	
		Cables included	AC
		Manual	✓

Power		Certificates	
Input frequency	50/60 Hz	Compliance certificates	CE, REACH, RoHS, UKCA
Input current	1.5 A	Certification	UKCA, CE, RoHS, REACH, ErP
Maximum power	100 W	Logistics data	
Maximum output voltage	12 V	Warranty period	2 year(s)
Minimum output voltage	5 V		
Output voltage accuracy (±)	5%		
AC adapter power	100 W		



4002888734417

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-FEB-2025. Prints or copies of Information are only valid on the printed Publication date