

DELL OptiPlex 7020 Intel® Core™ i3 i3-14100T 8 GB DDR5-SDRAM 512 GB SSD Ubuntu Linux MFF Mini PC Must

Brand : DELL Product family: OptiPlex Product code:

N003O7020MFFEMEA_VP_UBU

Product name: 7020

DELL OptiPlex 7020. Protsessori perekond: Intel® Core™ i3, Protsessori mudel: i3-14100T. Sisemälu: 8 GB, Sisemälu tüüp: DDR5-SDRAM. Salvestusmaht kokku: 512 GB, Salvestusseade: SSD. Pardagraafika adapteri mudel: Intel UHD Graphics 730. WiFi. Installitud operatsioonisüsteem: Ubuntu Linux. Toiteallikas: 90 W. Keretüüp: MFF. Toote tüüp: Mini PC. Toote värv: Must





Processor	Ports & interfaces	
Processor manufacturer * Intel	Ethernet LAN (RJ-45) ports	1
Processor family * Intel® Core™ i3	Combo headphone/mic port	✓
Processor generation Intel® Core™ i3 (14th gen)	DC-in jack	✓
Processor model * i3-14100T	Design	
Processor cores 4	•	MEE
Processor threads 8	Chassis type *	MFF
Processor boost frequency 4.4 GHz	Placement supported	Horizontal/Vertical
Performance cores 4	Cable lock slot	•
Performance-core Max Turbo Frequency 4.4 GHz	Cable lock slot type Product colour *	Kensington Black
Performance-core base frequency 2.7 GHz	Performance	
Processor cache 12 MB	Market positioning	Business
Processor cache type Smart Cache	Motherboard chipset	Intel Q670
Number of processors installed 1	Audio chip	Realtek ALC3204
Processor base power 35 W	Built-in speaker(s)	√
Maximum turbo power 69 W	Number of speakers	1
Memory	· ·	·
Internal memory * 8 GB	Password protection	•
Maximum internal memory * 64 GB	Trusted Platform Module (TPM)	•
Internal memory type DDR5-SDRAM	Trusted Platform Module (TPM) version	2.0
Memory layout (slots x size) 1 x 8 GB	Product type *	Mini PC
Memory slots 2x SO-DIMM		
Storage	Software	
Total storage capacity * 512 GB	Operating system installed *	Ubuntu Linux
Storage media * SSD	Power	
Optical drive type *	Power supply *	90 W
Total SSDs capacity 512 GB	Power supply input voltage	100 - 240 V
Number of SSDs installed 1	Power supply input frequency	50/60 Hz
SSD capacity 512 GB	Operational conditions	
SSD interface PCI Express	Operating temperature (T-T)	10 - 35 °C
NVMe ✓	Storage temperature (T-T)	-40 - 65 °C
SSD form factor M.2	Operating relative humidity (H-H)	20 - 80%
Graphics	Storage relative humidity (H-H)	5 - 95%
Discrete graphics card *	Operating altitude -15.2 - 30	-15.2 - 3048 m
Discrete graphics card · 💢	Non-operating altitude	-15.2 - 10668 m
On-board graphics card *	.ton operating articade	

Graphics		Operational conditions	
Discrete graphics card model * Not available On-board GPU manufacturer Intel On-board graphics card family Intel® UHD Graphics	Non-operating vibration Operating shock Non-operating shock	1.37 G 40 G 105 G	
On-board graphics card model *	Intel UHD Graphics 730	Sustainability	
Network		Sustainability compliance	✓
Ethernet LAN * Ethernet LAN data rates	✓ 10,100,1000 Mbit/s	Sustainability certificates	TCO, ENERGY STAR, EPEAT Climate +
Wi-Fi *	✓	Doesn't contain	PVC/BFR
Top Wi-Fi standard	Wi-Fi 6E (802.11ax)	Weight & dimensions	
Wi-Fi standards	802.11a, Wi-Fi 5 (802.11ac), 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E (802.11ax)	Width * Depth *	36 mm 178 mm
WLAN controller manufacturer	Intel	Height *	182 mm
WLAN controller model	Intel Wi-Fi 6E AX211	Packaging content	
Antenna type	2x2	Display included *	×
Ports & interfaces		Cables included	AC
USB 2.0 ports quantity *	2	Carbon footprint	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3	Total carbon footprint (kg of CO2e)	91
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1	Carbon emissions, manufacturing (kg of CO2e)	59
PowerShare	✓	Carbon emissions, logistics (kg of CO2e)	2
Number of USB ports with PowerShare support	1	Carbon emissions, energy usage (kg of CO2e)	28
HDMI ports quantity *	1	Carbon emissions, end-of-life (kg of	1
HDMI version	1.4b	CO2e)	_
DisplayPorts quantity	1	Total carbon emissions, w/o use phase (kg of CO2e)	62
DisplayPort version	1.4a	PAIA version	GaBi version 1, 2024

