

## Lindy 43400 jaotur USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Must

Brand: Lindy Product code: 43400

**Product name:** 43400

Lindy 43400. Hostiliides: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Jaoturi liidesed: USB 3.2 Gen 1 (3.1 Gen 1) Type-C. Andmeedastuskiirus: 5000 Mbit/s, Toote värv: Must, Korpuse materjal: Akrüülnitriil butadieen stüreen (ABS). Toite tüüp: DC (alalisvool). Kaal: 260 g, Konnektori 1 mõõtmed (LxSxK): 41,1 x 16,5 x 9,5 mm, Konnektori 2 mõõtmed (LxSxK): 67,5 x 22 x 13,5 mm. Kogus pakis: 1 tk, Pakendi laius: 236 mm, Pakendi sügavus: 255 mm





| Ports & interfaces  |   | Weight & dimensions  |  |
|---|---|--|--|
| Host interface * Hub interfaces * USB 3.2 Gen 1 (3.1 Gen 1) Type-C  | USB 3.2 Gen 1 (3.1 Gen 1) Type-C<br>USB 3.2 Gen 1 (3.1 Gen 1) Type-C<br>1   | Weight Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)   | 260 g<br>41.1 x 16.5 x 9.5 mm<br>67.5 x 22 x 13.5 mm     |
| ports quantity  Ports quantity *  | 2   | Packaging data   |  |
| Features  Data transfer rate *  Product colour  Housing material  | 5000 Mbit/s<br>Black<br>Acrylonitrile butadiene styrene   | Quantity per pack Package width Package depth Package weight Package type  | 1 pc(s) 236 mm 255 mm 300 g Polybag                      |
| LED indicators  | (ABS)<br>✓  | Packaging content  | , 3  |
| Cable type<br>AWG wire size   | Round cable 26 Polyvinyl chloride (PVC) 3 m 6.5 mm Tinned copper Nickel  Twisted pair CE, FCC, RoHS & REACH, CP65 | Manual<br>Quick start guide  | ✓<br>✓   |
| Cable jacket material Cable length Cable diameter Conductor material Connector contacts plating Plug and Play Transmission medium Certification |   | Operational conditions Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Technical details | 0 °C<br>40 °C<br>0 - 40 °C<br>32 - 104 °F<br>-10 - 60 °C |
|   | CL, I CC, NOTIS & NEACH, CF 05  | Constitution of the same   | CE, Federal Communications                               |
| <b>Power</b> Power supply type  | DC  | Compliance certificates  | Commission (FCC), REACH, RoHS                            |



4002888434003

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.