

Axagon ADSA-M2C HDD/SSD dokkimisjaam USB 3.2 Gen 2 (3.1 Gen 2) Type-C Must

Brand : Axagon

Product code: ADSA-M2C

Product name : ADSA-M2C

Axagon ADSA-M2C. Varunduse meedia tüüp: SSD, Ketta liides: M.2, Toetatud ketaste suurused: M.2. Hostiliides: USB 3.2 Gen 2 (3.1 Gen 2) Type-C. Toote värv: Must, Materjal: Alumiinium, Maksimaalne andmeedastuskiirus: 10 Gbit/s. AC-sisendpinge: 100 - 240 V, Väljundpinge: 5 V, Väljundvool: 3 A. Toetatud Windowsi operatsioonisüsteemid: Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1, Toetatud Linux'i operatsioonisüsteemid: Kernel 2.6.31, Kernel 2.6.33, Toetatud Maci operatsioonisüsteemid: Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac...



Hard drive		Software	
Storage media type *	SSD	Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8, Windows 8.1
Storage drive interface *	M.2	Linux operating systems supported	Kernel 2.6.31, Kernel 2.6.33
Storage drive sizes supported *	M.2	Mac compatibility	✓
Number of storage drives supported	2		
Ports & interfaces			Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C	Mac operating systems supported	
DC-in jack	✓		
Features		Weight & dimensions	
Product colour	Black	Width	68 mm
Material	Aluminium	Depth	17 mm
Maximum data transfer rate	10 Gbit/s	Height	68 mm
Plug and Play	✓	Weight	94 g
Hot-Plug support	✓	Packaging data	
S.M.A.R.T. support	✓	Package width	93 mm
TRIM support	✓	Package depth	65 mm
LED indicators	✓	Package height	170 mm
On/off switch	✓	Package weight	353 g
UASP support	✓	Package type	Box
Certification	FCC, CE, RoHS	Packaging content	
Cooling		AC adapter included	✓
Built-in fan	✗		
Power			
AC input voltage	100 - 240 V		
Output voltage	5 V		
Output current	3 A		

Packaging content	
Cables included	USB Type-A to USB Type-C, USB Type-C to USB Type-C
Manual	✓
Other features	
Connection to PC	✓
Compliance certificates	CE, RoHS
Logistics data	
Country of origin	China



8595247906496

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-FEB-2025. Prints or copies of Information are only valid on the printed Publication date