



TP-Link Omada EAP650-Wall 3000 Mbit/s Valge Power over Ethernet tugi

Brand : TP-Link

Product family: Omada

Product code: EAP650-WALL

Product name : EAP650-Wall

TP-Link Omada EAP650-Wall. 2,4 GHz, 5 GHz, Andmete edastamise maksimaalne määr: 3000 Mbit/s. Turvaalgoritmid: SNMP, SSH, WPA-Enterprise, WPA2-Enterprise. Ethernet LAN-i andmeedastuskiirused: 10,100,1000 Mbit/s. Power over Ethernet tugi. Toote värv: Valge



| Features | | Power | |
|---|--|-----------------------------------|-----------|
| 2.4 GHz * | ✓ | DC voltage range | 12 V |
| 5 GHz * | ✓ | Design | |
| 6 GHz * | ✗ | Placement * | Wall |
| Maximum data transfer rate * | 3000 Mbit/s | Product colour * | White |
| Maximum data transfer rate (2.4 GHz) | 574 Mbit/s | Reset button | ✓ |
| Maximum data transfer rate (5 GHz) | 2402 Mbit/s | LED indicators | ✓ |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Antenna | |
| Frequency band | 2.4 - 5 GHz | Antenna type * | Internal |
| Networking standards | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3af, IEEE 802.3at | Certificates | |
| | | Certification | CE, RoHS |
| Number of users | 100 user(s) | Weight & dimensions | |
| Automatic channel selection | ✓ | Width | 86 mm |
| Automatic channel scanning | ✓ | Depth | 86 mm |
| VLAN support | ✓ | Height | 42.6 mm |
| Rate limiting | ✓ | Packaging data | |
| Band steering | ✓ | Package width | 127 mm |
| Airtime Fairness (ATF) | ✓ | Package depth | 139 mm |
| Quality of Service (QoS) support | ✓ | Package height | 55 mm |
| Security | | Package weight | 290 g |
| Security algorithms * | SNMP, SSH, WPA-Enterprise, WPA2-Enterprise | Package type | Box |
| MAC address filtering | ✓ | Packaging content | |
| Number of SSID supported | 16 | Quantity per pack | 1 pc(s) |
| Remote Authentication Dial-In User Service (RADIUS) | ✓ | Quick start guide | ✓ |
| | | Operational conditions | |
| | | Operating relative humidity (H-H) | 10 - 920% |

| Ports & interfaces | | Operational conditions | |
|------------------------------|---|---------------------------------|-------------|
| Ethernet LAN (RJ-45) ports * | 2 | Operating temperature (T-T) | 0 - 40 °C |
| Power | | Storage temperature (T-T) | -40 - 70 °C |
| Power over Ethernet (PoE) * | ✓ | Storage relative humidity (H-H) | 5 - 90% |



4897098682104



4897098683569

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-FEB-2025. Prints or copies of Information are only valid on the printed Publication date