## Canon i-SENSYS MF754CDW Laser A4 1200 x 1200 DPI 33 lk/min WiFi

Brand : Canon

Product family: i-SENSYS

Product code: 5455C009

Product name : MF754CDW

Canon i-SENSYS MF754CDW. Printimistehnoloogia: Laser, Printimine: Värviline printimine, Maksimaalne resolutsioon: 1200 x 1200 DPI. Kopeerimine: Värviline kopeerimine, Maksimaalne kopeerimisresolutsioon: 600 x 600 DPI. Skaneerimine: Värviskaneerimine, Optilise skaneerimise resolutsioon: 600 x 600 DPI. Faksimine: Värviline faksimine. Dupleksfunktsioonid: Skaneerimine. Maksimaalne ISO A-seeria paberi suurus: A4. WiFi. Toote värv: Valge





Printing		Paper handling	
Print technology * Printing * Maximum resolution * Print speed (black, normal quality,	Laser Colour printing 1200 x 1200 DPI 33 ppm	ISO B-series sizes (B0B9) Non-ISO print media sizes Envelopes sizes Paper tray media weight	B5 Executive, Letter, Statement C5, Com-10, DL, Monarch 60 - 200 g/m <sup>2</sup>
A4/US Letter) * Warm-up time	14 s	Ports & interfaces	
Time to first page (black, normal) Time to first page (colour, normal)	7.1 s 7.1 s	USB port USB 2.0 ports quantity	✓ 1
Copying		Network	
Duplex copying * Copying * Maximum copy resolution * Maximum number of copies Copier resize ID-card copy function	<ul> <li>Colour copying</li> <li>600 x 600 DPI</li> <li>999 copies</li> <li>25 - 400%</li> </ul>	Wi-Fi * Ethernet LAN * Ethernet LAN data rates Wi-Fi standards Security algorithms	<ul> <li>10,100,1000 Mbit/s</li> <li>802.11b, 802.11g, Wi-Fi 4 (802.11n)</li> <li>64-bit WEP, 128-bit WEP, WPA-AES,</li> <li>WPA-PSK, WPA-TKIP, WPA2-AES,</li> <li>WPA2-PSK, WPA2-TKIP</li> </ul>
Scanning		Management protocols	SNMPv1, SNMPv3 (IPv4,IPv6)
Duplex scanning *✓Scanning *Colour scanningOptical scanning resolution *600 x 600 DPIScanner type *ADF scannerScan toCloud, E-mail, FTP, USBInput colour depth24 bitOutput colour depth24 bit	Colour scanning 600 x 600 DPI ADF scanner Cloud, E-mail, FTP, USB	Performance Internal memory * Built-in processor Processor frequency Sound power level (printing) Sound power level (standby)	1024 MB ✓ 1200 MHz 65 dB 41 dB
Greyscale levels	256	Design	
Scan drivers –	ica, twain, wia	Product colour * Market positioning *	White Business
Fax Faxing * Modem speed Fax memory Speed dialling	Colour faxing 33.6 Kbit/s 512 pages	Built-in display * Display Control type Colour display	✓ LCD Touch ✓

Features		Power	
Recommended duty cycle Maximum duty cycle * Duplex functions * Printing colours *	750 - 4000 pages per month 50000 pages per month Scan Black, Cyan, Magenta, Yellow	Power consumption (max) Power consumption (printing) Power consumption (standby) Power consumption (sleep)	1380 W 700 W 24 W 1 W
Input & output capacity		Energy Star Typical Electricity Consumption (TEC)	0.3 kWh/week
Total number of input trays *	1	AC input voltage	220 - 240 V
Total input capacity * Total output capacity *	250 sheets 150 sheets	AC input frequency	50 - 60 Hz
Multi-Purpose tray	✓ 50 sheets	System requirements	
Multi-Purpose tray input capacity		supported 8.1 Mac OS X 10.12 Sierr 10.13 High Sierra, Ma Mojave, Mac OS X 10 Mac OS X 10.15.3 Ca	Windows 10, Windows 11, Windows 8.1
Auto document feeder (ADF) Auto document feeder (ADF) input capacity	✔ 50 sheets		Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina,
Maximum input capacity	850 sheets		Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3
Paper handling		Mac operating systems supported	Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.5 Leopard, Mac OS X 10.6
Maximum ISO A-series paper size * Paper tray media types *	A4 Coated paper, Envelopes, Heavy paper, Plain paper, Postcard, Recycled paper, Thin paper	Snow Leopard, Mac OS X Mac OS X 10.8 Mountain L OS X 10.9 Mavericks, Mac	Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
ISO A-series sizes (A0A9) *	A4, A5, A6	Linux operating systems supported	<ul> <li>Image: A second s</li></ul>
		Server operating systems supported	Windows Server 2022, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	10 - 30 °C

Weight & dimensions

425 mm

461 mm

430 mm

23.3 kg

Width

Depth

Height

Weight



4549292193152

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.