



APC BR900MI puhvertoiteallikas (UPS) Liini-interaktiivne 0,9 kVA 540 W 6 vahelduvvoolu kontakt

Brand : APC

Product code: BR900MI

Product name : BR900MI

APC BR900MI. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 0,9 kVA, Väljundvõimsus: 540 W. AC-väljundi tüüp: C13 pistikut, Elektripistik: C14 pistikut, AC-väljundite arv: 6 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Aku kasutusiga (max): 5 aasta(t), Aku laadimisaeg: 12 h. Toote kuju: Tower, Toote värv: Must, Kaabli pikkus: 1,83 m. Sertifikaat: A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI




Features		Design	
UPS topology *	Line-Interactive	Cable length	1.83 m
Output power capacity *	0.9 kVA	Cooling type	Passive
Output power *	540 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	176 V	LED indicators	✓
Input operation voltage (max) *	294 V		
Input frequency *	50/60 Hz		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Maximum current	10 A		
Response time	12 ms		
ECO mode	✓		
Noise level	45 dB		
Surge protection	✓		
Surge protection features	Network		
Audible alarm(s)	✓		
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm		
Ports & interfaces		Operational conditions	
AC outlet types	C13 coupler	Operating temperature (T-T)	0 - 40 °C
Power plug	C14 coupler	Storage temperature (T-T)	-15 - 45 °C
AC outlets quantity	6 AC outlet(s)	Operating relative humidity (H-H)	0 - 95%
USB port	✓	Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Certificates	
		Certification	A-tick, C-tick, CE, EAC, GS Mark, RCM, TISI
		Packaging content	
		Cables included	USB cable
		Manual	✓
		Sustainability	
		Sustainability certificates	Green Premium
		Weight & dimensions	
		Width	91 mm

Ports & interfaces		Weight & dimensions	
Ethernet LAN (RJ-45) ports	2	Depth	310 mm
Cabling technology	10/100/1000Base-T(X)	Height	190 mm
Battery		Weight	7.1 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Battery life (max)	5 year(s)	Package width	440 mm
Battery recharge time	12 h	Package depth	143 mm
Hot-swap battery	✓	Package height	255 mm
Automatic battery test	✓	Package weight	8 kg
Cold start	✓	Logistics data	
Design		Harmonized System (HS) code	85078000
Form factor *	Tower	Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304346944



731304346944

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.