



APC SMC1000I-2UC puhvertoiteallikas (UPS) Liini-interaktiivne 1 kVA 600 W 4 vahelduvvoolu kontakt

Brand : APC

Product code: SMC1000I-2UC

Product name : SMC1000I-2UC



APC SMC1000I-2UC. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 1 kVA, Väljundvõimsus: 600 W. AC-väljundi tüüp: C13 pistikut, Elektripistik: C14 pistikut, AC-väljundite arv: 4 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Aku kasutusiga (max): 6 aasta(t), Aku laadimisaeg: 3 h. Toote kuju: Riilulile monteeritav, Toote värv: Must, Püstiku mahutavus: 2U. Vastavussertifikaadid: RoHS, Sertifikaat: CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH

Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	1 kVA	Rack capacity	2U
Output power *	600 W	Cable length	2.44 m
Waveform *	Sine	Product colour *	Black
Input operation voltage (min) *	170 V	Display type	LCD
Input operation voltage (max) *	300 V	Operational conditions	
Input frequency *	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (min)	220 V	Storage temperature (T-T)	-15 - 45 °C
Output operation voltage (max)	240 V	Operating relative humidity (H-H)	0 - 95%
Output frequency	50/60 Hz	Storage relative humidity (H-H)	0 - 95%
Automatic Voltage Regulation (AVR)	✓	Operating altitude	0 - 3000 m
Surge energy rating	680 J	Non-operating altitude	0 - 15000 m
Output voltage Total Harmonic Distortion (THD)	5%	Certificates	
Noise level	41 dB	Compliance certificates	RoHS
Surge protection	✓	Certification	CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH
Audible alarm(s)	✓	Packaging content	
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Rack mount kit	✓
Ports & interfaces		Cables included	RJ-45, RS-232
AC outlet types	C13 coupler	Sustainability	
Power plug	C14 coupler	Sustainability certificates	ENERGY STAR, Green Premium
AC outlets quantity	4 AC outlet(s)	Weight & dimensions	
USB port	✓	Width	432 mm
USB 2.0 ports quantity	1	Depth	406 mm
Serial interface	✓	Height	86 mm
Serial interface type	RS-232	Weight	20.5 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
SmartSlot	✓	Resource CD	✓
Battery		Software CD	✓
Battery technology	Sealed Lead Acid (VRLA)	Package width	535 mm
Number of batteries supported	1	Package depth	570 mm
Battery life (max)	6 year(s)	Package height	235 mm
Battery recharge time	3 h	Package weight	20.7 kg
Replacement battery cartridge	APCRBC124	Logistics data	
		Products per pallet	16 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	945.86



0731304332930



731304332930

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-FEB-2025. Prints or copies of Information are only valid on the printed Publication date