iiyama ProLite XU2793HS-B7 PC lamekuvar 68,6 cm (27") 1920 x 1080 pikslit Full HD LED Must

Brand : iiyama **Product family:** ProLite **Product code:** XU2793HS-B7

Product name: XU2793HS-B7

iiyama ProLite XU2793HS-B7. Ekraani diagonaal: $68,6 \text{ cm } (27^{\circ})$, Ekraani resolutsioon: 1920×1080 pikslit, HD tüüp: Full HD, Ekraani tehnoloogia: LED, Ekraani pind: Matt, Reaktsiooniaeg: 1 ms, Loomulik kuvasuhe: 16:9, Vaatenurk, horisontaalne: 178° , Vaatenurk, vertikaalne: 178° . Sisseehitatud kõlar(id). VESA paigaldamine. Toote värv: Must





Pixel pitch 0.311 x 0.311 mm Horizontal scan range 30 - 110 kHz Viewable size, horizontal 59.8 cm Colour gamut standard NTSC, sRGB sRGB coverage (typical) 96% NTSC coverage (typical) 72% Performance VESA Adaptive Sync support Flicker-free technology NTSC colours of the total standard to the total				
Display resolution* 1920 x 1080 pixels DisplayPort version 1.2 HD type* Full HD Headphone out* ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓	lay		Ports & interfaces	
Panel type * IPS Touchscreen * X Display brightness (typical) 300 cd/m² Panel mounting interface 100 x 100 mm Response time * 1 ms Wall mountable ✓ Response time (MPRT) 1 ms Cable management ✓ Display surface Matt Cable lock slot * ✓ Screen shape * Flat Cable lock slot type Kensington Contrast ratio (typical) * 1300:1 Height adjustment * X Contrast ratio (dynamic) 8000000:1 Tilt adjustment * X Contrast ratio (dynamic) 178° On Screen Display (OSD) ✓ Viewing angle, vertical 178° On Screen Display (OSD) ✓ Display number of colours * 16.7 million colours Pixel pitch 0.311 x 0.311 mm Horizontal scan range 30 · 110 kHz Viewable size, horizontal 33.6 cm Viewable size, vertical 59.8 cm Colour gamut standard NTSC, sRGB Energy efficiency class (SDR) * Energy efficiency class (SDR) * Energy efficiency class (HDR) * Not available Energy consumption (SDR) per 1000 hours * Power consu	lay resolution * ype * ve aspect ratio *	1920 x 1080 pixels Full HD 16:9	DisplayPort version Headphone out *	1.2 •
Touchscreen* X VESA mounting* Panel mounting interface 100 x 100 mm Panel mounting interface Panel mounting interface 100 x 100 mm Panel mounting interface 100 x 100 mm Panel mounting interface 100 x 100 mm Panel mounting interface Panel mounting interface 100 x 100 mm Panel mounting interface Panel specific included in the panel of panel in the pane	, ,,		Ergonomics	
Pixel pitch O.311 x 0.311 mm Horizontal scan range 30 - 110 kHz Viewable size, horizontal Viewable size, vertical Colour gamut standard SRGB coverage (typical) NTSC, sRGB SRGB coverage (typical) NTSC coverage (typical) Performance VESA Adaptive Sync support Flicker-free technology Power Power Energy efficiency class (SDR) * Energy efficiency class (HDR) * Not available Energy consumption (SDR) per 1000 22 kWh hours * Power consumption (typical) * Power consumption (standby) * O.5 W AC input voltage 100 - 240 V AC input frequency 50/60 Hz	chscreen * lay brightness (typical) conse time * conse time (MPRT) lay surface en shape * crast ratio (typical) * crast ratio (dynamic) fimum refresh rate * cring angle, horizontal cring angle, vertical	X 300 cd/m² 1 ms 1 ms 1 ms Matt Flat 1300:1 80000000:1 100 Hz 178° 178°	Panel mounting interface Wall mountable Cable management Cable lock slot * Cable lock slot type Height adjustment * Tilt adjustment Tilt angle range On Screen Display (OSD)	100 x 100 mm ✓ ✓ ✓ Kensington X ✓ 4 - 22°
Viewable size, horizontal 33.6 cm Power Viewable size, vertical 59.8 cm Energy efficiency class (SDR) * Energy efficiency class (HDR) * Not available Colour gamut standard NTSC, sRGB Energy efficiency class (HDR) * Not available sRGB coverage (typical) 96% Energy consumption (SDR) per 1000 hours * NTSC coverage (typical) 72% Power consumption (typical) * 22 W Performance Power consumption (standby) * 0.5 W VESA Adaptive Sync support ✓ Power consumption (off) 0.3 W Flicker-free technology ✓ AC input voltage 100 - 240 V AC input frequency 50/60 Hz	•		on sereen bisplay (03b) languages	
Viewable size, vertical 59.8 cm Energy efficiency class (SDR)* E Colour gamut standard NTSC, sRGB Energy efficiency class (HDR)* Not available sRGB coverage (typical) 96% Energy consumption (SDR) per 1000 hours * 22 kWh NTSC coverage (typical) 72% Power consumption (typical)* 22 W Performance Power consumption (standby)* 0.5 W VESA Adaptive Sync support ✓ Power consumption (off) 0.3 W Flicker-free technology ✓ AC input voltage 100 - 240 V AC input frequency 50/60 Hz			Power	
Performance Power consumption (standby) * 0.5 W VESA Adaptive Sync support ✓ Power consumption (off) 0.3 W Flicker-free technology ✓ AC input voltage 100 - 240 V AC input frequency 50/60 Hz	able size, vertical 59.8 cm ur gamut standard NTSC, sRGB s coverage (typical) 96%	Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours *	Not available 22 kWh	
Flicker-free technology AC input voltage 100 - 240 V AC input frequency 50/60 Hz	ormance		• • • • • • • • • • • • • • • • • • • •	
Power supply type Internal	. ,		Power consumption (off) AC input voltage AC input frequency	100 - 240 V 50/60 Hz

Multimedia		Power	
Number of speakers	2	Energy efficiency scale	A to G
RMS rated power	2 W	Weight & dimensions	
Built-in speaker(s) *	✓	Width (with stand)	611.5 mm
Built-in camera *	×	Depth (with stand)	189 mm
Design		Height (with stand)	435 mm
Market positioning *	Business	Weight (with stand)	3.8 kg
Product colour *	Black	Packaging data	
Ports & interfaces		Package width	688 mm
Built-in USB hub *	×	Package depth	125 mm
HDMI *	✓	Package height	465 mm
HDMI ports quantity	1	Package weight Package type	5.3 kg Box
HDMI version	1.4	rackage type	BOX



4948570124626

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.