

## GIGABYTE B650M GAMING PLUS WIFI AMD B650 Protsessoripesa AM5 Mikro ATX


**Brand :** GIGABYTE

**Product code:** B650M GAMING PLUS WF

**Product name :** B650M GAMING PLUS WIFI



GIGABYTE B650M GAMING PLUS WIFI. Protsessori tootja: AMD, Protsessori pesa: Protsessoripesa AM5, Ühilduvad protsessoriseeriad: AMD Ryzen 7000 Series, AMD Ryzen 8000 Series, AMD Ryzen 9000 Series. Toetatud mälutüübid: DDR5-SDRAM, Maksimaalne sisemälu: 256 GB, Mälupesatüüp: DIMM. Kõvaketta ühenduse tüüp: M.2, PCI Express 4.0, SATA III, Toetatud ketaste tüübid: HDD & SSD, RAID-tasemed: 0, 1, 10. Maksimaalne resolutsioon: 4096 x 2160 pikslit. Ethernet-liidese tüüp: 2.5 Gigabit Ethernet, LAN-kontroller: Realtek RTL8125, Wi-Fi standard: Wi-Fi 6E (802.11ax)



Processor		Network	
Processor manufacturer *	AMD	Ethernet LAN	✓
Processor socket *	Socket AM5	Ethernet interface type	2.5 Gigabit Ethernet
Compatible processor series *	AMD Ryzen 7000 Series, AMD Ryzen 8000 Series, AMD Ryzen 9000 Series	LAN controller	Realtek RTL8125
Supported processor sockets	Socket AM5	Wi-Fi *	✓
<b>Memory</b>		Top Wi-Fi standard	Wi-Fi 6E (802.11ax)
Supported memory types *	DDR5-SDRAM	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)
Number of memory slots *	4	WLAN controller model	Realtek RTL8852CE
Memory slots type	DIMM	Bluetooth	✓
Memory channels	Dual-channel	Bluetooth version	5.3
ECC compatibility	Non-ECC	<b>Features</b>	
Supported memory clock speeds	8000,7800,7600,7200,7000,6800,6600,6400,6200,6000,5600,5200,4800 MHz	Motherboard chipset *	AMD B650
Supported memory clock speed (max)	8000 MHz	Audio chip	Realtek ALC897
Maximum internal memory *	256 GB	Audio output channels *	7.1 channels
Unbuffered memory	✓	Product colour	Dark brown
Maximum internal memory per slot	64 GB	PC health monitoring	Fan, Temperature, Voltage
<b>Storage controllers</b>		Component for *	PC
Supported storage drive types	HDD & SSD	Motherboard form factor *	micro ATX
Supported storage drive interfaces *	M.2, PCI Express 4.0, SATA III	Motherboard chipset family *	AMD
Number of HDDs supported	4	Cooling type	Passive
Number of storage drives supported	6	Power source type	ATX
RAID support	✓	Windows operating systems supported	Windows 10 x64, Windows 11 x64
RAID levels	0, 1, 10	<b>Expansion slots</b>	
<b>Graphics</b>		PCI Express x1 (Gen 3.x) slots	1
Parallel processing technology support *	Not supported	PCI Express x16 (Gen 4.x) slots	1
Maximum resolution	4096 x 2160 pixels	Number of M.2 (M) slots	2
HDCP	✓		
DirectX version	12.0		

Internal I/O		Expansion slots	
USB 2.0 connectors *	2	1st M.2 largest key size	2580
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	2	1st M.2 highest PCI Express generation	4.0
Number of SATA III connectors *	4	2nd M.2 largest key size	22110
Front panel audio connector	✓	2nd M.2 highest PCI Express generation	4.0
Front panel connector	✓	<b>BIOS</b>	
ATX Power connector (24-pin)	✓	BIOS type *	UEFI AMI
CPU fan connector	✓	BIOS memory size	256 Mbit
Number of CPU fan connectors	1	ACPI version	5.0
Number of chassis fan connectors	2	Clear CMOS jumper	✓
EPS power connector (8-pin)	✓	Desktop Management Interface (DMI) version	2.7
Number of EPS power connectors (8-pin)	1	System Management BIOS (SMBIOS) version	2.7
TPM connector	✓	<b>Logistics data</b>	
RGB LED pin header	✓	Products per shipping (inner) case	1 pc(s)
Number of RGB LED pin headers	3	<b>Battery</b>	
<b>Rear panel I/O ports</b>		Battery weight	3 g
USB 2.0 ports quantity *	2	Lithium weight per battery	0.07 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3	Number of battery cells	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity *	1	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
Ethernet LAN (RJ-45) ports *	1	Battery type	CR2032
PS/2 ports quantity	1	<b>Packaging data</b>	
HDMI ports quantity *	1	Package width	270 mm
HDMI version	2.1	Package depth	268 mm
DisplayPorts quantity	2	Package height	68 mm
DisplayPort version	1.4	Package weight	1.53 kg
Headphone outputs	1	<b>Weight &amp; dimensions</b>	
Line-in	✓	Width	244 mm
Microphone in	✓	Depth	244 mm
WiFi-AP antenna jack	2	Height	35 mm
		<b>Packaging content</b>	
		Batteries included	✓
		Antenna included	✓
		Screws included	✓
		Bundled software	Norton® Internet Security (OEM version) LAN bandwidth management software
		<b>Other features</b>	
		Weight	1.44 kg
		<b>Technical details</b>	
		Warranty period	3 year(s)



4719331862213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-FEB-2025. Prints or copies of Information are only valid on the printed Publication date