

DELL P5525QC Digital signage lameekraan 138,8 cm (54.6") LCD $400\ cd/m^2\ 4K\ Ultra\ HD\ Must$

Brand : DELL Product code: 210-BNTN

Product name: P5525QC

DELL P5525QC. Tootedisain: Digital signage lameekraan. Ekraani diagonaal: 138,8 cm (54.6"), Ekraani tehnoloogia: LCD, Ekraani resolutsioon: 3840 x 2160 pikslit, Ekraani heledus: 400 cd/m², HD tüüp: 4K Ultra HD. Toote värv: Must





Display		Audio	
Panel type	IPS	Built-in speaker(s) *	✓
LED backlight	✓	Number of built-in speakers	2
LED backlighting type	Edge-LED	RMS rated power	20 W
Display diagonal *	138.8 cm (54.6")	Design	
Display technology * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio Response time Contrast ratio (typical) Viewing angle, horizontal	LCD 3840 x 2160 pixels 400 cd/m² 4K Ultra HD x 16:9 8 ms 1200:1 178°	Product design * Placement supported * Product colour * VESA mounting * Panel mounting interface Bezel width (bottom) Bezel width (side) Bezel width (top)	Digital signage flat panel Indoor Black ✓ 300 x 400 mm 2.85 cm 1.89 cm 1.89 cm
Viewing angle, vertical	178°	Anti-glare screen	✓
Display number of colours	1.07 billion colours	Performance	
Pixel pitch	0.315 x 0.315 mm	Purpose *	Commercial
Active display area (W x H) Display diagonal (metric)	1209.6 x 680.4 mm 138.787 cm	Power	
Horizontal scan range Vertical scan range	138.787 cm 30 - 140 kHz 24 - 75 Hz	Power consumption (typical) * Power consumption (standby) *	77.1 W 0.5 W
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Power consumption (off) Power consumption (max) Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours AC input voltage	0.3 W 300 W F 77 kWh 100-240 V
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	AC input frequency Energy efficiency scale	50/60 Hz A to G
Colour depth	8 bit	,	
Native refresh rate	60 Hz		

Display		Weight & dimensions	
Haze rate Surface hardness Colour gamut	25% 3H 72%	Display width Display depth Display height Display weight	1247.4 mm 79.8 mm 727.8 mm 22.4 kg
Ports & interfaces			22.7 kg
HDMI ports quantity * HDMI version	2 2.0	Packaging data Package weight	33.8 kg
DVI port *	×	Packaging content	
DisplayPorts quantity *	2	Remote control included	✓
DisplayPort version USB port *	1.4	Cables included	AC, DisplayPort, HDMI, USB, USB Type-C
USB version	3.2 Gen 1 (3.1 Gen 1)	Operational conditions	
USB 2.0 Type-B ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	USB Type-A, USB Type-B, USB Type-C 1	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 10 - 80% -20 - 60 °C 5 - 90%
USB 3.2 Gen 1 (3.1 Gen 1) Type-C	2	Technical details	
ports quantity USB Power Delivery (USB PD) USB Power Delivery up to USB Type-C DisplayPort Alternate	✓ 90 W	Sustainability certificates Doesn't contain Compliance certificates	ENERGY STAR, TCO Arsenic, Mercury, PVC/BFR RoHS
Mode Ethernet LAN *	/	Other features	
Ethernet LAN (RJ-45) ports RS-232C	1	Quick start guide Remote control battery	AAA x 2
DC-in jack	✓		

