Samsung LH105QPD5BGXEN infoekraan 2,67 m (105") WiFi 500 cd/m 2 5K Ultra HD Must Tizen 7.0 24/7

Brand : Samsung **Product code:** LH105QPD5BGXEN

Product name: LH105QPD5BGXEN

Samsung LH105QPD5BGXEN. Ekraani diagonaal: 2,67 m (105"), Ekraani resolutsioon: 5120 x 2160 pikslit, Ekraani heledus: 500 cd/m², HD tüüp: 5K Ultra HD. WiFi. Töötunnid (tunnid/päevad): 24/7. Installitud operatsioonisüsteem: Tizen 7.0. Toote värv: Must





| Display | | Design | |
|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|--------------------------------------------|
| Panel type Display diagonal * Display resolution * | VA 2.67 m (105") 5120 x 2160 pixels 500 cd/m² 5K Ultra HD 21:9 6 ms 4000:1 | Product colour * VESA mounting * Panel mounting interface | Black ✓ 1000 x 400 mm |
| Display brightness * HD type * Native aspect ratio Response time Contrast ratio (typical) | | Performance Operating hours (hours/days) HDCP HDCP version | 24/7 • 2.2 |
| Dynamic contrast ratio marketing name | Mega Contrast | Power | |
| Viewing angle, horizontal Viewing angle, vertical Pixel pitch Horizontal scan range | 178° 178° 0.1595 x 0.4785 mm 30 - 81 kHz | Power consumption (typical) * Power consumption (standby) * AC input voltage AC input frequency | 550 W 0.5 W 100 - 240 V 50/60 Hz |
| Vertical scan range | 48 - 75 Hz | Computer system | |
| Ports & interfaces | | Internal memory Operating system installed | 16 GB Tizen 7.0 |
| HDMI ports quantity * HDMI version DVI port * DisplayPorts quantity * DisplayPort version USB port * | 3 2.1 X 1 1.4 | Weight & dimensions Display width Display depth Display height Display weight | 2484.3 mm 48.1 mm 1068 mm 55.6 kg |
| USB ports quantity | 3 | Packaging data | |
| Ethernet LAN * Ethernet LAN (RJ-45) ports Wi-Fi * RS-232 interface | ✓ 1 ✓ | Package width Package depth Package height Package weight | 2668 mm 275 mm 1190 mm 78.1 kg |
| Design | | Operational conditions | |
| Placement supported * | Indoor | Operating temperature (T-T) Operating relative humidity (H-H) | 0 - 40 °C 10 - 80% |



8806095807201

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.