

## APC SMT3000IC puhvertoiteallikas (UPS) Liini-interaktiivne 3 kVA 2700 W 9 vahelduvvoolu kontakt

Brand : APC Product code: SMT3000IC

**Product name:** SMT3000IC


APC SMT3000IC. Puhvertoiteallika topoloogia: Liini-interaktiivne, Väljundvõimsuse potentsiaal: 3 kVA, Väljundvõimsus: 2700 W. AC-väljundi tüüp: C13 pistikut, C19 pistikut, Elektripistik: C20 pistikut, AC-väljundite arv: 9 vahelduvvoolu kontakt. Akutehnoloogia: Suletud pliiaku (VRLA), Tüübipärane varundamisaeg täiskoormusega: 5,1 min, Tüübipärane varundamisaeg poole koormusega: 17,2 min. Toote kuju: Tower, Toote värv: Must, Kaabli pikkus: 1,83 m. Vastavussertifikaadid: RoHS, Sertifikaat: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOLI





Features		Battery	
UPS topology *	Line-Interactive	Cold start	✓
Output power capacity * Output power *	3 kVA 2700 W	Design	
Waveform * S Input operation voltage (min) * 1 Input operation voltage (max) * 3 Input frequency * 5	Sine 151 V 302 V 50/60 Hz 220 V	Form factor * Cable length Product colour * Display type LED indicators	Tower 1.83 m Black LCD Status
Output operation voltage (max)	240 V	Operational conditions	
Output frequency 50/60 Hz Automatic Voltage Regulation (AVR)   Surge energy rating 365 J  Efficiency 98.4%  Emergency Power Off (EPO)   Noise level 53 dB	✓ 365 J 98.4% ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Audible alarm(s)	✓	Certificates	
Auto-restart	✓	Compliance certificates	RoHS
Ports & interfaces AC outlet types	C13 coupler, C19 coupler	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOLI
Power plug	C20 coupler	Packaging content	
AC outlets quantity  Number of output IEC jumpers	9 AC outlet(s) 2	Cables included	RS-232, USB cable
USB port	<b>✓</b>	Quick installation guide	✓
SmartSlot	<b>✓</b>	Sustainability	
Battery		Sustainability certificates	Green Premium
Battery technology	Sealed Lead Acid (VRLA)	Weight & dimensions	
Typical backup time at full load	5.1 min	Width	197 mm

Battery		Weight & dimensions	
Typical backup time at half load	17.2 min	Depth	544 mm
Battery life (max)	5 year(s)	Height	435 mm
Battery recharge time	3 h	Weight	52.5 kg
Hot-swap battery	✓	Packaging data	
Automatic battery test		Package width	381 mm
		Package depth	762 mm
		Package height	699 mm
		Package weight	63.7 kg
		Logistics data	
		Products per pallet	9 pc(s)
		Harmonized System (HS) code	85078000
		Total carbon footprint (kg of CO2e)	3335.07





731304337331

0731304337331

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.